

L^AT_EX Class for The *Annals of Mathematics*^{*}

Boris Veytsman[†]

2025/03/06, v1.33

Abstract

This package provides a class for typesetting articles for The *Annals of Mathematics*

Contents

1	Introduction	3
2	User's Guide	3
2.1	Installation	3
2.2	Invocation	4
2.3	Top Matter	5
2.3.1	Commands for Authors	5
2.3.2	Commands for Editors	6
2.4	Additional Macros	9
2.5	Theorems	10
2.6	Illustrations and color	11
2.7	Funding	11
2.8	Bibliography	11
2.9	Papers in languages other than English	12
3	Implementation	14
3.1	Identification	14
3.2	Options	14
3.3	Loading Class and Packages	15
3.4	Internationalization	16
3.5	Fonts	17
3.6	Page Dimensions and Paragraphing	18
3.7	Headers	19
3.8	Top Matter Macros	20
3.9	Typesetting Top Matter	26
3.10	Typesetting End Matter	29
3.11	Sectioning	30
3.12	Figures and Tables	31
3.13	Theorems	31

^{*}©2010–2025, Princeton University (Mathematics Department)

[†]borisv@lk.net, boris@varphi.com

3.14 Bibliography Macros	32
3.15 Additional Macros	33
3.16 End of Class	35

1 Introduction

The *Annals of Mathematics* is published bimonthly with the cooperation of Princeton University and the Institute for Advanced Study. Founded in 1884 by Ormond Stone of the University of Virginia, the journal was transferred in 1899 to Harvard University, and in 1911 to Princeton University. Since 1933, the Annals has been edited jointly by Princeton University and the Institute for Advanced Study (see <http://annals.princeton.edu/annals/about/journal/about.html>).

This class presents a complete redesign of the journal style—with new fonts and new interface.

An author well acquainted with AMS^AT_EX should find this package easy to use and configurable. The User Manual below illustrates the basic use of the class and discusses the differences with *amsart*. For an in-depth tutorial of AMS^AT_EX I could recommend the excellent book [1].

2 User’s Guide

2.1 Installation

The installation of the class follows the usual practice [2] for L^AT_EX packages:

1. Run `latex` on `aomart.ins`. This will produce the file `aomart.cls`.
2. Put the file `aomart.cls` to the place where L^AT_EX can find them (see [2] or the documentation for your T_EX system).
3. Update the database of file names. Again, see [2] or the documentation for your T_EX system for the system-specific details.
4. The file `aomart.pdf` provides the documentation for the package (this is the file you are probably reading now).

As an alternative to items 2 and 3 you can just put the files in the working directory where your `.tex` file is.

The class uses some other L^AT_EX classes or packages. Most probably, they are already installed on your system. If not (or if their versions are very old), you need to download and install them. Here is the list:

1. `amsart` class and related packages [3],
2. Package `hyperref` [4],
3. `ifpdf` package [5],
4. `fancyhdr` package [6],
5. `cmtiup` package [7] for “special italics” with upright digits and punctuation. Note that since many distributions do not include this package, you may need to install it yourself. Just download the file <http://mirrors.ctan.org/fonts/cm/cmtiup.zip>, unzip it in your TEXMF directory and rebuild the file names database with the command like `mktexlsr`,
6. `yhmath` package [8].

2.2 Invocation

To use the class, put in the preamble of your document

```
\documentclass[<options>]{aomart}
```

The class internally loads `amsart`, so all facilities of `amsart` [1, 9] can be used in the source.

The class should work with the `Babel` [10] package. At present, English, French and German languages are fully supported. See also Section 2.9.

options The options `draft` and `final` work in the same way as for `amsart` and standard `LATeX`. If the option `draft` is chosen, the overfull lines are marked by black boxes on the margins and the `\includegraphics` prints blank placeholders for the images. The option `final` (default) switches off the marking of overfull lines and restores the behavior of `\includegraphics`. To switch on just the overfull marks, without changing the behavior of `\includegraphics`, one can either explicitly pass the option `final` to `graphics` package:

```
\documentclass[draft]{aomart}  
\usepackage[final]{graphics}
```

or add in the beginning of the document

```
\overfullrule=5pt
```

option The option `manuscript` is intended to facilitate the communications between `manuscript` the editor and the author. It enables two things:

1. Numbering of lines in the manuscript is switched off in the normal mode, but is on in the manuscript mode.
2. Command `\EditorialComment` is no-op in normal mode, but produces marginal commentaries in the manuscript
3. Hyperlinks are black in normal mode, but blue in manuscript mode.

option The option `screen` is intended for the onscreen version of the article. If this `screen` option is selected, the links are blue colored, and the margins are reduced.

option Starting from version 1.9 (2011) the formatting of DOI numbers changed according to the new recommendations from CrossRef. The option `olddoi` switches on the “old” formatting. It is used for compatibility reasons.

option Starting from version 1.5 (2016) the formatting of DOI numbers changed again according to Crossref recommendations. The option `doi2016` switches to the version existed between 2011 and 2016.

option Since June 2017 keywords and AMS Mathematical Subjects classification numbers are printed on the title page. The option `oldkeywords` suppresses this.

options The size-changing options of `amsart` class (8pt, 9pt, ..., 12pt) have no effect other than producing a warning in the log since the journal is designed for only 9pt one type size (roughly corresponding to 11pt of `amsart`).

10pt Normally the scheme for MSC numbers is not printed. If the option *11pt* `printscheme` is chosen, however, it is printed explicitly.

12pt

option

`printscheme`

2.3 Top Matter

There are two kinds of top matter commands: the ones used primarily for authors and the ones used primarily for editors. We describe them separately.

The macros described below must be issued in the preamble of the document, i.e. before `\begin{document}`. They produce fatal error otherwise. This behavior is required by the way non-T_EX scripts process the files to produce metadata.

The only exception is abstract, which should be placed after `\begin{document}`.

2.3.1 Commands for Authors

`\title` The command `\title`, as in `amsart` class, has two arguments: one optional, and one mandatory:

```
\title[<ShortTitle>]{<FullTitle>}
```

The mandatory argument is the full title of the article. The optional argument, if present, defines the shorter version of the title for running heads. If the optional argument is absent, the full title is used instead.

The optional argument should be used in two cases: when the full title is too long to fit in the running head, *and* when the author wants to add a footnote or linebreaks to the title.

`\author` The interface for specifying the authors and their affiliations is close the the `\email` one of `amsart` [11] (and different from the standard L^AT_EX). For each author a `\address` separate command `\author` should be used, followed by `\address` and (optionally) `\curraddr` `\currauthor`, `\email`, `\urladdr` and `\orcid`. Note that the house style of the `\urladdr` *Annals of Mathematics* requires writing `\address` in the form *Institution, City*, `\orcid` *State* (or *Institution, City, Country* for non-US locations). Like the newer versions of `amsart`, `aomart` does *not* require the doubling of the @ symbols in the e-mail addresses. The macro `\author` has two arguments, similarly to `\title`:

```
\author[<AbbrevName>]{<FullName>}
```

The optional argument defines the shorter form of the author's name to be included in the running head.

`\givenname` The papers published in the *Annals of Mathematics* are included in various `\surname` databases. For the indexing purposes it is important to correctly separate the authors' names into "First Name/Surname" parts. This operation is not easy for the computers. Therefore we decided that the authors should know best how to deal with their names. The macros `\givenname` and `\surname` are used to indicate how to split the name into the parts.

`\fulladdress` Another command which does not affect the typesetting is `\fulladdress`. It is used to store the full mailing address of the author for the online version of the journal and various databases.

`\contrib` Sometimes there are contributors to a paper, who are not full authors: the person may write an appendix or other part of the paper. You can use the command `\contrib[<role>]{<name>}` for indicating these persons. Note that [<role>] argument has a special meaning, indicating that the role of this person is the same as for the previous contributor, for example,

```
\contrib[with Appendix~A by]{A. U. Thor}
\givenname{Alexandra}\surname{Thor}
\contrib{A. N. Other}
```

```
\givenname{Antony N.}\surname{Other}
\contrib[with Appendix~B by]{Y. Etanother}
\givenname{Yakov}\surname{Ethanother}
```

In this example Appendix A is written by A. U. Thor and A. N. Another, and Appendix B is written by Y. Ethanother. Commands `\orcid`, `\email`, `\address`, `\fulladdress`, `\givenname` and `\surname` can be used for contributors in the same way they are used for authors.

\shortauthors In some cases the authors list may be too long for the running head, even if the abbreviated forms are used for each author. In this case it is possible to change the running head by a *redefinition* of the command `\shortauthors`. This redefinition must be done after all `\author` commands, but before `\maketitle`:

```
\renewcommand{\shortauthors}{A.~Smith et al}
```

\thanks Like `amsart` (and unlike standard L^AT_EX), `aomart` allows `\thanks` only *outside* of commands `\title` and `\author`.

\copyrightnote Normally each paper is copyrighted by Department of Mathematics, Princeton University. This is reflected in the footnote on the first page of the article. However, by arrangement with the editors, certain papers may have different copyright. The command `\copyrightnote{\textcopyright~2012 by the authors. This paper may be reproduced, in its entirety, for noncommercial purposes.}`, if issued, changes the footnote to the corresponding text, for example:

```
\copyrightnote{\textcopyright~2012 by the authors. This paper may be reproduced, in its entirety, for noncommercial purposes.}
```

Note that if you issue this command, you should explicitly include both the copyright sign and the year unless the paper does not have a copyright, for example:

```
\copyrightnote{This paper is in the public domain}
```

abstract (env.) The abstract of the paper must be put between `\begin{abstract}` and `\end{abstract}`. Unlike the situation in `amsart` class, abstract may be put *after* `\maketitle`.

A paper may have several abstracts in different languages. This situation is discussed in Section 2.9.

\maketitle The macro `\maketitle` typesets the top matter. All top matter information should be specified before this command.

2.3.2 Commands for Editors

The commands described in this section should be used by the editors to insert the information about the published paper. They must be put before the `\maketitle` command.

\keyword The command `\keyword` adds a keyword to the list of keywords. This command may be repeated, for example

```
\keyword{Embedding theorem}
\keyword{Relatively hyperbolic group}
```

\subject The command `\subject` has three parameters: whether the subject is primary or secondary, the classification scheme and the subject itself, for example

```
\subject{primary}{msc2000}{20E45}  
\subject{secondary}{msc2000}{20F65}
```

\formatdate The macro `\formatdate` is used to format the dates in the commands. Its argument is the date in the format `YYYY-MM-DD`, for example

```
\formatdate{2010-08-13}
```

\received The commands `\received`, `\revised`, `\accepted`, `\published`, `\publishedonline` accept as a parameter a date in the form `\formatdate{(YYYY-MM-DD)}`, for

\accepted example

\published
\publishedonline `\received{\formatdate{2004-12-24}}
\revised{\formatdate{2006-04-12}}
\accepted{\formatdate{2007-10-02}}`

\proposed The macros `\proposed`, `\seconded`, `\corresponding`, `\editor`, `\version` are used to set the corresponding metadata for the editorial process, for example

\corresponding
 \editor `\proposed{E. D. Itor}
\seconded{A. S. Sociate}
\corresponding{A. U. Thor}`
 \version `\version{2.1}`

\volumenumber The macros `\volumenumber`, `\issuenumber`, `\publicationyear`, `\papernumber`,
\issuenumber `\startpage`, `\endpage` set up the corresponding data for the paper, for example:
\publicationyear
 \papernumber `\volumenumber{172}
\issuenumber{1}`
 \startpage `\publicationyear{2010}
\papernumber{1}`
 \endpage `\startpage{1}
\endpage{39}`

Note that if the argument of `\endpage` is empty, L^AT_EX tries to calculate the last page number as best as it can.

\copyrightyear In the standard copyright statement the copyright year is assumed to be the same as the `\publicationyear`. However, for special cases one can set the copyright year explicitly, for example,

```
\publicationyear{2012}  
\copyrightyear{2011}
```

Note that if you use your own copyright statement instead of the canned one (with the command `\copyrightnote`), you need to put there the copyright year explicitly instead of using this command.

\doinumber The macros `\doinumber`, `\mrnumber` and `\zblnumber` set the information

\mrnumber

\zblnumber

\arxivnumber

about paper in four major reference databases: DOI (<http://www.doi.org/>), MathSciNet (<http://www.ams.org/mathscinet/>), Zentralblatt MATH (<http://www.zentralblatt-math.org/zmath/>) and arXiv (<https://www.arxiv.org>). The use of these macros should be obvious:

```
\doinumber{10.1215/S0012-7094-92-06520-3}
\mrnumber{1154181}
\zblnumber{0774.14039}
\arxivnumber{1234.567890}
```

Note the difference between these commands and the bibliography commands discussed in Section 2.8. Commands in this Section set up the data for the *current article*. Commands in Section 2.8 set up the data for the articles in the bibliography list.

Normally you should *not* use `\doinumber` command, since the class will construct the standard DOI for the paper from the volume, issue and paper information. Use it *only* if the result is by any reason wrong.

`\oldsubsections` Starting with version 1.2 we decreased the vertical spacing before `\subsection`. The command `\oldsubsections` restores the “old” values.

The class has a system of editorial comments and highlighting for communication between copy editors, production editors, journal editors and authors. All these comments are visible only in the `manuscript` mode. In production environment they are not displayed.

The important feature of these commands is the notion of **audience**. Each comment or highlighting has an audience in mind, which is the optional argument of the comments and highlights. One can selectively enable the comments for the given audience. There is a special audience called `default`, which is enabled, well, by default. All other audiences must be enabled explicitly.

`\EditorialComment` The macro `\EditorialComment[⟨audience⟩]{⟨comments⟩}` typesets the comments on the margins in the `manuscript` mode for the selected audience, for example,

```
Erd\"os proved the following theorem.\EditorialComment{A citation is
needed}
```

```
Erd\"os proved the following
theorem^\cite{Erd01}.\EditorialComment[Editor]{Please check the
citation}
```

`\Highlight` The macro `\Highlight[⟨audience⟩]{⟨text⟩}` highlights the `text` for the selected **audience**. The highlighting is done using the color selected for the given audience, for example

```
This is described by the following
theorem\Highlight{::}\EditorialComment{Added ``::''}
```

```
This is described by the following
theorem\Highlight[Editor]{::}\EditorialComment[Editor]{Do we need
``::'' here?}
```

Code	Example
<code>\widetilde{AB}</code>	\widetilde{AB}
<code>\widehat{AB}</code>	\widehat{AB}
<code>\widetriangle{AB}</code>	\widetriangle{AB}
<code>\wideparen{AB}</code>	\wideparen{AB}
<code>\widering{AB}</code>	\widering{AB}
<code>\widebar{AB}</code>	\widebar{AB}

Table 1: Wide Mathematical Accents

\ECSelect The audiences to be displayed are selected by the command `\ECSelect{\langle audiences\rangle}` with the comma separated list of audiences, for example,

```
\ECSelect{Editor,Author}
```

The audience “default” is selected by default.

\HSelect The command `\HSelect[\langle color\rangle]{\langle audience\rangle}` selects the audience for which the highlight is intended. The optional argument “color” is used for highlighting, for example,

```
\HSelect[green]{Editor}
```

The audience “default” is selected by default.

2.4 Additional Macros

eqnarray (env.) The class `aomart` loads the class `amsart`. Therefore all familiar `amsmath` commands [9] are available. In particular, there are many commands for writing multiline equations (`split`, `align`, `gather`, `multiline`, …). The environments `eqnarray` and `eqnarray*`, while still available, are *not* recommended and should be avoided if possible.

\widetilde A number of “wide” mathematical accents is available due to the (internally loaded) package `yhmath` [8]: `\widetilde`, `\widehat`, `\widetriangle`, `\wideparen`, `\widetriangle`, `\widering`, `\widebar`. See Table 1 for the example of the usage.

\wideparen A set of macros is used to make more convenient clickable references in the online versions of papers. The package `hyperref` [4] makes clickable reference numbers `\widebar` in the phrases like

```
\fullref ...in theorem~\ref{thm:Noeter}...
\pfullref ...see equation~\eqref{eq:alpha}...
\bfullref
```

\fullpageref However, it is more convenient for the readers if both the number *and* the word “theorem” or “equation” were clickable. The macros `\fullref` solve this problem. Each macro has two arguments: the word and the reference, for example

```
...in \fullref{theorem}{thm:Noeter}...
```

The command `\pfullref` typesets the reference in parentheses. The command `\bfullref` typesets it in brackets, and the command `\eqfullref` uses the `\eqref` command, for example,

```
...see \eqfullref{equation}{eq:alpha}...
```

The similar command `\fullpageref` is used to make the word “page” clickable, for example,

```
...see \eqfullref{equation}{eq:alpha} on  
\fullpageref{eq:alpha}...
```

By default the command adds the word “page” to the text. You can override this choice using the optional parameter, e.g.

```
\fullpageref[The page]{eq:alpha} starts the discussion of...
```

The Perl script `fullref.pl` can be used to convert change all references to the `\fullref` commands. It works in the following way:

```
perl fullref.pl original.pl > result.pl
```

The script converts all instances of combinations “word `\ref{reference}`”, “word`\ref{reference}`” and “word`\pageref{reference}`” to “`\fullref{word}{reference}`”, and similarly for parenthesized references, `\eqref` commands, and page references. To prevent the converting, just put `\ref{reference}` or `\eqref{reference}` inside braces. The “word” here must not start with a backslash (i.e. must not be a macro itself). This prevents disastrous results for phrases like “`see~\ref{a}`, `\ref{b}`”.

The distribution includes two sample files, `aomsample.tex` and `aomsample1.tex`, the latter being obtained from the former by the script `fullref.pl`.

Note that `\autoref` command of `hyperref` provides for another mechanism that achieves the same goal. Unlike `\fullref` command, the command `\autoref` tries to figure out the name of the reference from the context. See the manual [4] for more information.

2.5 Theorems

`\newtheorem` You can use the commands of `amsthm` package [12] like `\newtheorem{lem}{Lemma}` for numbered theorems, or `\newtheorem*[KL]{Klein's Lemma}` for unnumbered theorems, or tune the numbering using the optional arguments of these commands.

To provide backward compatibility with some other classes used internally by the *Annals of Mathematics*, the class provides yet another optional argument for the command `\newtheorem`, allowing constructions like `\newtheorem[\it]{lem}{Lemma}`. This optional parameter is not used in our typesetting.

The class provides two theorem styles:

plain: This is the default theorem style. It is used for Theorem, Lemma, Proposition, Conjecture, Corollary and Claim.

definition: This style is used for Definition, Remark, Notation, Condition, Example etc.

Note that AMS classes define the third theorem style, **remark**. In our class remarks are typeset in the **definition** style. To make the authors' lives easier we define the theorem style **remark**, which is identical to the theorem style **definition**.

2.6 Illustrations and color

The authors can use the `graphics`, `graphicx`, `PSTricks`, `pgf/tikz`, `Metapost` or other tools to include illustrations (see [13] for a comprehensive discussion of L^AT_EX graphics possibilities).

`\includecolorgraphics` The printed edition of the journal cannot use color illustrations. The online version can, although we recommend against the reliance of color since it might not be accessible for people with color perception problems. If you want to use color illustrations for the online version, you need to prepare two versions, a color one, and a BW (or grayscale one) with *identical sizes and contents*. The command `\includecolorgraphics[<options>]{<color_file>} {<bw_file>}` can be used to select the proper illustration: in the screen mode the color one is chosen, and otherwise the bw one is chosen.

2.7 Funding

`\funding` There is a special command for showing the support for the paper, `\funding[<text>]{<sponsor>}{<grantid>}`. Normally it prints the name of the sponsor and in parentheses the id of the grant, if it is not empty. However, you can override this using the optional argument of the command. For example, the following text

```
AB is grateful to \funding{NASA}{123GH456}, while MJ was supported  
by \funding{NIH}{}. Both authors acknowledge \funding[the generous  
help of other agencies]{Department of Defense}{Special project  
grant}.
```

will expand to

```
% AB is grateful to NASA (123GH456), while MJ was supported  
by NIH. Both authors acknowledge the generous  
help of other agencies.
```

The command will save the information about the grants in the form suitable for automatic processing.

2.8 Bibliography

The authors are encouraged to use BibT_EX for uniform style of bibliography. The distribution includes the BST files `aomplain bst` and `aomalpha bst`. These files have several additional non-standard fields:

mrnumber: MathSciNet number for the article.

zblnumber: Zentralblatt number for the article.

doi: DOI number for the article.

jfmnumber: JFM number for the article.

arxiv: ArXiv reference for the ArXiv manuscript.

url: If the reference is available online, the corresponding url.

venue: (for conference entries) The place where the conference took place.

sortyear: Some entries do not have a year set up (e.g. some *unpublished* entries). If you have several entries from the same author, some with a year, and some without, you may want to put them in a certain order. The field **sortyear** overrides **year** for the sorting purposes.

titlenote: this field is like **note**, but is typeset immediately after a title. It should be used for additional information, for example,

```
@Book{Knuth94:TheTeXbook,
  author = {Knuth, Donald Ervin},
  title = {The \TeX book},
  publisher = {Addison-Wesley Publishing Company},
  year = 1994,
  series = {Computers \& Typesetting A},
  address = {Reading, MA},
  titlenote = {with illustrations by Duane Bibby}
}
```

totalpages: some articles (especially published in an electronic format) do not have start and end page numbers; instead you may put the total number of pages. If both **pages** and **totalpages** are present, **pages** take precedence.

\doi There are several databases routinely used in the science and mathematics communities. Among them are DOI, MathSciNet, Zentralblatt, Jahrbuch Database, ArXiv. Many bibliographies include references to these databases. The commands \jfm \doi, \mr, \zbl, \jfm, \arxiv are used to typeset these references. If you use \arxiv BibTeX, these commands are automatically used for the corresponding fields in your database entries.

2.9 Papers in languages other than English

The recommended way to typeset papers in languages other than English is *babel* package [10]. For example, to typeset a paper in French (with an English abstract, see below), one puts in the preamble

```
\usepackage[utf8]{inputenx}
\usepackage[english,frenchb]{babel}
```

Such papers often contain several abstracts: for example, in the language the paper is written *and* in English. Accordingly, *aomart* allows several abstracts. Each abstract must be put inside a group with the corresponding language selected using \selectlanguage command, for example

```
{\selectlanguage{french}}%
```

```
\begin{abstract}
    French abstract
\end{abstract}

{\selectlanguage{english}%
\begin{abstract}
    English abstract
\end{abstract}}
```

3 Implementation

3.1 Identification

We start with the declaration who we are. Most .dtx files put driver code in a separate driver file .drv. We roll this code into the main file, and use the pseudo-guard <gobble> for it.

```
1 <class>\NeedsTeXFormat{LaTeX2e}
2 {*gobble}
3 \ProvidesFile{aomart.dtx}
4 />gobble<
5 <class>\ProvidesClass{aomart}
6 [2025/03/06 v1.33 Typesetting articles for the Annals of Mathematics]
```

And the driver code:

```
7 {*gobble}
8 \documentclass{ltxdoc}
9 \usepackage{array,booktabs,amsmath,graphics}
10 \let\widebar\overline
11 \usepackage{url}
12 \usepackage{amsfonts,yhmath}
13 \usepackage[breaklinks,colorlinks,linkcolor=black,citecolor=black,
14           pagecolor=black,urlcolor=black,hyperindex=false]{hyperref}
15 \PageIndex
16 \CodelineIndex
17 \RecordChanges
18 \EnableCrossrefs
19 \begin{document}
20   \DocInput{aomart.dtx}
21 \end{document}
22 />gobble<
23 {*class}
```

3.2 Options

The size-changing options produce a warning:

```
24 \long\def\@aom@size@warning#1{%
25   \ClassWarning{aomart}{Size-changing option #1 will not be
26     honored}}%
27 \DeclareOption{8pt}{\@aom@size@warning{\CurrentOption}}%
28 \DeclareOption{9pt}{\@aom@size@warning{\CurrentOption}}%
29 \DeclareOption{10pt}{\@aom@size@warning{\CurrentOption}}%
30 \DeclareOption{11pt}{\@aom@size@warning{\CurrentOption}}%
31 \DeclareOption{12pt}{\@aom@size@warning{\CurrentOption}}%
```

\if@aom@manuscript@mode Check whether we are in the manuscript mode

```
32 \newif\if@aom@manuscript@mode
33 \@aom@manuscript@modefalse
34 \DeclareOption{manuscript}{\@aom@manuscript@modetrue}
```

\if@aom@screen@mode Check whether we are in the screen mode

```
35 \newif\if@aom@screen@mode
36 \@aom@screen@modefalse
37 \DeclareOption{screen}{\@aom@screen@modetrue}
```

```

\if@aom@olddoi DOI processing is different in the “old” and new mode.
38 \newif\if@aom@olddoi
39 \Qaom@olddoifalse
40 \DeclareOption{olddoi}{\Qaom@olddoittrue}

\if@aom@doiMMXVI DOI processing is different in the 2016 and new mode
41 \newif\if@aom@doiMMXVI
42 \Qaom@doiMMXVIfalse
43 \DeclareOption{doi2016}{\Qaom@doiMMXVItrue}

\if@aom@oldkeywords Keywords processing is different in the “old” and new mode.
44 \newif\if@aom@oldkeywords
45 \Qaom@oldkeywordsfalse
46 \DeclareOption{oldkeywords}{\Qaom@oldkeywordstrue}

\if@aom@printscheme
47 \newif\if@aom@printscheme
48 \Qaom@printschemefalse
49 \DeclareOption{printscheme}{\Qaom@printschemetrue}

All other options are passed to amsart:
50 \DeclareOption*{\PassOptionsToClass{\CurrentOption}{amsart}}
Now we read the configuration file
51 \InputIfFileExists{aomart.cfg}{%
52   \ClassInfo{aomart}{%
53     Loading configuration file aomart.cfg}}{%
54   \ClassInfo{aomart}{%
55     Configuration file aomart.cfg is not found}}
And process the options:
56 \ProcessOptions\relax

```

3.3 Loading Class and Packages

```

\@makefnmark@kernel AMS redefines \@makefnmark. Here we return to the kernel version
57 \let\@makefnmark@kernel\@makefnmark

We start with the base class
58 \LoadClass[11pt]{amsart}

\@makefnmar Restoring the kernel version
59 \let\@makefnmark\@makefnmark@kernel

\@citet We redeine this macro early in case some package wants to patch it. Basically
house style for repeated citations is not [1, 2, 3], but [1], [2], and [3].
Note that we do not want to use \andify since it requires fine control of
expansion. Rather, we just count the number of commas. Below \tempcnta is
the total number of cites, and \tempcntb is the current cite.
60 \def\@citet[#1]#2{\leavevmode
61   \tempcnta=0
62   \Qfor\@citetb:=#2\do{\advance\tempcnta by 1}%
63   \tempcntb=1

```

```

64  \let\@citea\@empty
65  \@cite{\@for\@citeb:=#2\do
66    {\@citea\def\@citea[], []%
67     \advance\@tempcntb by 1
68     \ifnum\@tempcnta=\@tempcntb\relax
69       \ifnum\@tempcnta=2\relax
70         \def\@citea[] and~[]%
71       \else
72         \def\@citea[], and~[]%
73       \fi
74     \fi
75     \edef\@citeb{\expandafter\@firstofone\@citeb\@empty}%
76     \if@filesw\immediate\write\@auxout{\string\citation{\@citeb}}\fi
77     \ifundefined{b@\@citeb}{\hbox{\reset@font\bfseries ?}}%
78       \G@refundefinedtrue
79       \@latex@warning
80         {Citation ‘\@citeb’ on page \thepage \space undefined}%
81     {\@cite@ofmt{\csname b@\@citeb\endcsname}\}}\}}\#1\}}

```

A bunch of packages:

```

82 \RequirePackage{fancyhdr, lastpage, ifpdf, graphicx}
83 \RequirePackage[breaklinks,colorlinks]{hyperref}
84 \if@aom@screen@mode
85   \hypersetup{linkcolor=blue,citecolor=blue,
86   urlcolor=blue}%
87 \else\if@aom@manuscript@mode
88   \hypersetup{linkcolor=blue,citecolor=blue,
89   urlcolor=blue}%
90 \else
91   \hypersetup{linkcolor=black,citecolor=black,
92   urlcolor=black}%
93 \fi\fi
94 \urlstyle{rm}

```

Amsart has \collect@body macro. However, we want the \long version, so we use `environ`

```
95 \RequirePackage{environ}
```

3.4 Internationalization

There are some papers published in languages other than English. The Babel is expected to be used for them. Here we add some macros extending captions for these languages.

First, let us define English defaults:

\@aom@by This is just “By” in English:

```
96 \def\@aom@by{By}
```

\@aom@and This is “and” in English:

```
97 \def\@aom@and{and}
```

Now we can define internationalization:

```
98 \AtBeginDocument{\@ifpackageloaded{babel}{%
```

```

99  \addto\captionsfrench{\def\@aom@by{Par}\def\@aom@and{et}}%
100 \addto\captionsgerman{\def\@aom@by{Von}\def\@aom@and{und}}%
101 \addto\captionsenglish{\def\@aom@by{By}\def\@aom@and{and}}{}{}}
```

3.5 Fonts

We use `yhmath` for large symbols:

```
102 \RequirePackage{yhmath}
```

Since version 1.2 `ymath` no longer makes its large symbols default. We override this

```
103 \DeclareSymbolFont{largesymbols}{OMX}{yhex}{m}{n}
```

`\widehat` The way `\widehat` and `\widetilde` are implemented in `ymath` is buggy, see `\widetilde` https://www.reddit.com/r/TeX/comments/2j7mtn/usepackageamsmath_vs_usepackageyhmath_and_the/. We use AMS definitions instead

```

104 \xdef\widehat#1{\noexpand\mathmeasure{z@\textstyle{#1}}%
105   \noexpand\ifdim\noexpand\wd{z@}>\tw@ em%
106   \mathaccent"0\hexnumber@\symAMSb 5B{#1}%
107   \noexpand\else\mathaccent"0362{#1}\noexpand\fi}%
108 \xdef\widetilde#1{\noexpand\mathmeasure{z@\textstyle{#1}}%
109   \noexpand\ifdim\noexpand\wd{z@}>\tw@ em%
110   \mathaccent"0\hexnumber@\symAMSb 5D{#1}%
111   \noexpand\else\mathaccent"0365{#1}\noexpand\fi}
```

We need `cmtiup` package, but we may find out it is not installed.

```

112 \IfFileExists{cmtiup.sty}{%
113   \RequirePackage{cmtiup}}{%
114   \ClassWarning{aomart}{The package mputu is not found.\MessageBreak
115     You need this package to get italics with upright digits!}}
```

`\specialdigits` A legacy macro. We do not need it anymore.

```

116 \def\specialdigits{}%
117 \let\sishape=\itshape
118 \let\textsi=\textit
```

The `amsart` class defines several options for different font sizes (10pt, 11pt, etc). We have just one design size for the articles.

`\@typesizes` The font information in `amsart` is stored in `\@typesizes` macro. It has 11 typesizes: 5 below and 5 above `\normalsize`.

```

119 \def\@typesizes{%
120   \or{\@vipt}{9}\or{\@viupt}{9}\or{\@viiipt}{9}\or{\@ixpt}{12}%
121   \or{\@xpt}{13}%
122   \or{\@xipt}{14} \% normalsize
123   \or{\@xiipt}{15}\or{13}{17}\or{\@xviupt}{20}%
124   \or{19}{23.2}\or{22}{27.8}}%
125 \normalsize \lineskip=\baselineskip
```

`\widebar` The functionality of `\widebar` coincides with that of `amsmath \overline`:

```
126 \let\widebar\overline
```

3.6 Page Dimensions and Paragraphing

```
\textwidth These are from the old aomamlt2e:  
\textheight 127 \setlength{\textwidth}{31pc}  
128 \setlength{\textheight}{48pc}  
  
\evensidemargin The margins:  
\oddsidemargin 129 \oddsidemargin=.65in  
130 \evensidemargin=.65in  
  
\footins Some skips from aomamlt2e:  
\topskip 131 \setlength{\topskip}{12pt}  
\abovedisplayskip 132 \setlength{\abovedisplayskip}{6.95pt plus3.5pt minus 3pt}  
\belowdisplayskip 133 \setlength{\belowdisplayskip}{6.95pt plus4.5pt minus 3pt}  
134 \setlength{\skip\footins}{20pt}  
135 \setlength{\dimen\footins}{3in}  
  
\footskip Some space for footnotes:  
136 \setlength\footskip{30pt}  
  
\parskip Paragraph shape:  
\parindent 137 \setlength{\parindent}{22pt}  
138 \setlength{\parskip}{\z@}  
  
\widowpenalty We suppress widows and clubs:  
\clubpenalty 139 \widowpenalty=10000  
140 \clubpenalty=10000  
  
AMS defines the margins for lists \AtBeginDocument. Our lists are tighter  
141 \AtBeginDocument{  
142   \labelsep=5pt\relax  
143   \settowidth\leftmargini{\labelenumi\hskip\labelsep}%  
144   \leftmargin=\leftmargini  
145   \labelwidth=\leftmargini \advance\labelwidth-\labelsep  
146   \listi}  
  
\itemize  
147 \renewenvironment{itemize}{%  
148   \ifnum\@itemdepth>3 \@toodeep  
149   \else \advance\@itemdepth\@ne  
150     \edef\@itemitem{\labelitem\romannumeral\the\@itemdepth}%  
151     \list{\csname\@itemitem\endcsname}%  
152     {\settowidth\leftmargin{\labelitemi\hskip\labelsep}%  
153       \def\makelabel##1{\hss\llap{\upshape##1}}}%  
154   \fi  
155 }%  
156   \endlist  
157 }
```

3.7 Headers

```
\headsep Separation between the header and the body
158 \setlength{\headsep}{14pt}

\headheight Slightly increasing head height
159 \setlength{\headheight}{18.0pt}

\headrulewidth We do not want decorative rules in the journal:
\footrulewidth 160 \renewcommand{\headrulewidth}{0pt}
161 \renewcommand{\footrulewidth}{0pt}

\@aom@linecount This is the box displayed in the manuscript mode
162 \if@aom@manuscript@mode
163   \newsavebox{\@aom@linecount}
164   \savebox{\@aom@linecount}[4em][t]{\parbox[t]{4em}{%
165     \tempcnta\@ne\relax
166     \loop\ifnum\tempcnta<43\repeat\relax}}
167   \advance\tempcnta by \ifnum\tempcnta<43\repeat\relax
168 \fi
```

It is easy to set up headers with `fancyhdr`:

```
169 \pagestyle{fancy}
170 \fancyhead{}
171 \fancyfoot{}
172 \fancyhead[CO]{\scriptsize\shorttitle}
173 \fancyhead[RO,LE]{\footnotesize\thepage}
174 \if@aom@manuscript@mode
175   \fancyhead[LE]{\footnotesize\thepage\begin{picture}(0,0)%
176     \put(-26,-25){\usebox{\@aom@linecount}}%
177   \end{picture}}
178   \fancyhead[LO]{\begin{picture}(0,0)%
179     \put(-21,-25){\usebox{\@aom@linecount}}%
180   \end{picture}}
181   \fancyfoot[C]{\scriptsize Proof: page numbers may be temporary}
182 \fi
183 \fancyhead[CE]{\scriptsize\MakeUppercase\shortauthors}
```

The first page has the special headers. The style `firstpage` is invoked by `amsart`; here we just redefine it.

```
184 \fancypagestyle{firstpage}{%
185   \fancyhf{}%
186   \if@aom@manuscript@mode
187     \lhead{\begin{picture}(0,0)%
188       \put(-21,-25){\usebox{\@aom@linecount}}%
189     \end{picture}}
190   \fi
191   \chead{\scriptsize%
192     \href{\annalsurl}{Annals of Mathematics} \textbf{\currentvolume}%
193     (\currentyear),}
```

We always print the starting page. However, we print the last page only if it does not coincide with the first page. There are two cases here: first, the last page may still be `\pageref{LastPage}`. In this case we need to extract the numerical value

of the counter—note that hyperref is in action! Second, we could redefine the last page, and it is no longer `\pageref{LastPage}`. In this case we need to compare the value with the first page.

```

194   \start@page%
195   \def\tempa{\pageref{LastPage}}%
196   \edef\tempb{\start@page}%
197   \ifx\tempa\end@page
198     \edef\tempa{\HyPsd@@@pageref{LastPage}}%
199   \else
200     \edef\tempa{\end@page}%
201   \fi
202   \ifx\tempa\tempb\else--\end@page\fi\\
203 \ifx@\doinumber@\empty\else
204 \edef@\doinumber{\@doinumber}%
205 \expandafter\doi\expandafter{\@doinumber}\fi}%
206 \cfoot{\footnotesize\thepage}}%

```

`\annalsurl` The command to set up the URL of the journal
207 `\def\annalsurl#1{\gdef\@annalsurl{#1}}`
208 `\annalsurl{http://annals.math.princeton.edu/about}`

3.8 Top Matter Macros

We make these macros allowed only in the preamble:

```

209 \@onlypreamble{\title}
210 \@onlypreamble{\author}
211 \@onlypreamble{\contrib}
212 \@onlypreamble{\email}
213 \@onlypreamble{\address}
214 \@onlypreamble{\curraddr}
215 \@onlypreamble{\urladdr}
216 \@onlypreamble{\orcid}
217 \@onlypreamble{\givenname}
218 \@onlypreamble{\fulladdress}
219 \@onlypreamble{\surname}
220 \@onlypreamble{\thanks}
221 \@onlypreamble{\keyword}
222 \@onlypreamble{\subject}
223 \@onlypreamble{\received}
224 \@onlypreamble{\revised}
225 \@onlypreamble{\accepted}
226 \@onlypreamble{\published}
227 \@onlypreamble{\publishedonline}
228 \@onlypreamble{\proposed}
229 \@onlypreamble{\seconded}
230 \@onlypreamble{\corresponding}
231 \@onlypreamble{\editor}
232 \@onlypreamble{\version}
233 \@onlypreamble{\volumenumber}
234 \@onlypreamble{\issuenumber}
235 \@onlypreamble{\publicationyear}
236 \@onlypreamble{\copyrightnote}
237 \@onlypreamble{\copyrightyear}

```

```

238 \@onlypreamble{\papernumber}
239 \@onlypreamble{\startpage}
240 \@onlypreamble{\endpage}
241 \@onlypreamble{\doinumber}
242 \@onlypreamble{\mrnumber}
243 \@onlypreamble{\zblnumber}
244 \@onlypreamble{\arxivnumber}

```

Most top matter macros are defined in `amsart`. Here we just add some new macros and redefine some.

`\fulladdress` We store the information to output it later in the rpi file

```

\givenname 245 \def\@names{}
\surname 246 \def\givenname#1{\g@addto@macro\@names{givenname=#1;}}
247 \def\surname#1{\g@addto@macro\@names{surname=#1;}}
248 \def\fulladdress#1{\g@addto@macro\@names{fulladdress=#1;}}

```

`\author` We add mangling of `\@names` to the `amsart` macro

```

249 \renewcommand{\author}[2][]{%
250   \ifx\@empty\authors
251     \gdef\authors{\#2}%
252     \g@addto@macro\@names{author=\#2;}%
253   \else
254     \g@addto@macro\authors{\and\#2}%
255     \g@addto@macro\@names{\and author=\#2;}%
256   \fi
257   \gdef\aoa@current@orcid@target{\authors}%
258   \@ifnotempty{\#1}{%
259     \ifx\@empty\shortauthors
260       \gdef\shortauthors{\#1}%
261     \else
262       \g@addto@macro\shortauthors{\and\#1}%
263     \fi
264   }%
265   \g@addto@macro\addresses{\author{\#2}}%
266 }
267 \edef\author{\@nx\@dblarg
268   \@xp\@nx\csname\string\author\endcsname}

```

`\@currentcontribution` The current contribution

```
269 \def\@currentcontribution{}
```

`\@currentcontributors` The current contributors with the same contribution

```
270 \def\@currentcontributors{}
```

`\contribs` All contributors to the paper

```
271 \def\contribs{}
```

`\if@startcontribgroup` A switch whether the new group is started

```
272 \newif\if@startcontribgroup
273 \if@startcontribgroupfalse
```

```
\@processcurrentcontribgroup Add current contributors to \contributors
```

```
274 \def\@processcurrentcontribgroup{%
275   \ifx\@currentcontributors\empty\else
276     \def\@and{\upshape \oam@and}%
277     \author@andify\@currentcontributors
278     \ifx\contribs\empty\else
279       \g@addto@macro\contribs{\and}%
280     \fi
281     \expandafter\g@addto@macro\expandafter\contribs
282     \expandafter{\@currentcontribution}%
283     \g@addto@macro\contribs{\space}%
284     \expandafter\g@addto@macro\expandafter\contribs
285     \expandafter{\@currentcontributors}%
286   \fi
287 }
```

\contrib The processing of contributors. Contributors are separated into groups with the same contribution. Within the group one can omit the contribution.

```
288 \renewcommand{\contrib}[2][]{%
289   \def\@tempa{\#1}%
290   \gdef\aoam@current@orcid@target{\@currentcontributors}%
291   \startcontribgrouptrue
292   \ifx\@tempa\empty\relax
293     \ifx\@currentcontribution\empty\relax
294       \ClassError{aomart}{You must define contribution for
295         contributors}{The first \contrib command must have the
296         optional argument indicating the contribution}%
297     \else
298       \startcontribgroupfalse
299     \fi
300   \fi
301   \ifx\@currentcontribution\@tempa\relax
302     \startcontribgroupfalse
303   \fi
304   \if\@startcontribgroup
305     \@processcurrentcontribgroup
306     \gdef\@currentcontribution{\#1}%
307     \gdef\@currentcontributors{\#2}%
308   \else
309     \g@addto@macro\@currentcontributors{\and\#2}%
310   \fi
311   \g@addto@macro\@names{\and contributor=\#2;}%
312   \g@addto@macro\@names{role=}%
313   \expandafter\g@addto@macro\expandafter\%
314   \expandafter{\@currentcontribution}%
315   \g@addto@macro\@names{;}%
316   \g@addto@macro\addresses{\author{\#2}}%
317 }
```

\email We change amsart macro to output metadata

```
318 \renewcommand{\email}[2][]{%
319   \g@addto@macro\addresses{\email{\#1}{\#2}}%
320   \g@addto@macro\@names{email=\#2;}%
321 }
```

```

\urladdr We change amsart macro to output metadata
322 \renewcommand{\urladdr}[2][]{%
323   \g@addto@macro\addresses{\urladdr{\#1}{\#2}}%
324   \g@addto@macro\@names{\urladdr=\#2; }%
325 }

\aom@current@orcid@target Each new orcid can be added either to the authors or to the contributors. This
macro defines where it goes
326 \def\@aom@current@orcid@target{\authors}

\orcid Orcid also outputs metadata
327 \newcommand{\orcid}[1]{%
328   \g@addto@macro\addresses{\orcid{\#1}}%
329   \g@addto@macro\@names{\orcid=\#1; }%
330   \expandafter\g@addto@macro\@aom@current@orcid@target{\aom@orcidlink{\#1}}%
331 }

@aom@orcidlink The package orcidlink [14] requires TikZ, so here we reproduce its function-
ality using our own version of orcid logo. Note that the original logo is
licenses under CC0, see https://orcid.figshare.com/articles/figure/ORCID\_iD\_icon\_graphics/5008697
332 \newcommand\@aom@orcidlink[1]{\kern0.2ex\href{https://orcid.org/#1}{\includecolorgraphics[height=1em]{orcidlink}}}

\keyword Actually amsart has \kewords macro. It redefines \@keywords. Our macro adds
to the stack instead.
333 \def\@keyword#1{\ifx\@keywords\@empty\gdef\@keywords{\#1}\else
334   \g@addto@macro\@keywords{\, \#1}\fi}

\subject Subjects.
335 \let\@primarysubjects\@empty
336 \let\@secondarysubjects\@empty
337 \let\@primariescheme\@empty
338 \let\@secondarieschme\@empty
339 \def\@subject#1#2#3{%
340   \expandafter\ifx\csname @#1subjects\endcsname\@empty\relax
341     \expandafter\gdef\csname @#1subjects\endcsname{\#3}%
342   \else
343     \expandafter\g@addto@macro\csname @#1subjects\endcsname{\, \#3}%
344   \fi
345   \if@aom@printscheme
346     \expandafter\g@addto@macro\csname @#1subjects\endcsname{%
347       ^{(\#2)}%}
348   \fi}

\formatdate This just sends the date to the special macro \@formatdate
349 \def\@formatdate#1{\@formatdate#1\endformatdate}

\@formatdate This macro takes date in the form YYYY-MM-DD and properly formats it. Note
how we delete the leading zero in dates like April 02.
350 \def\@formatdate#1-#2-#3\endformatdate{%
351   \tempcnta=\#3\relax
352   \ifcase#2\or

```

```

353   January\or February\or March\or April\or May\or June\or
354   July\or August\or September\or October\or November\or December\fi
355   \space\the\@tempcnta,\space#1}

```

\received The following macros add stuff to the footnotes material:

```

\revised 356 \def\received#1{\def\@received{#1}}
\accepted 357 \let\@received\@empty
\published 358 \def\revised#1{\def\@revised{#1}}
\publishedonline 359 \let\@revised\@empty
360 \def\accepted#1{\def\@accepted{#1}}
361 \let\@accepted\@empty
362 \def\published#1{\def\@published{#1}}
363 \let\@published\@empty
364 \def\publishedonline#1{\def\@publishedonline{#1}}
365 \let\@publishedonline\@empty

```

The next macros mimic the functionality of `amsart \issueinfo` command.
Note that `\issueinfo` still works.

\volumenumber This sets the volume of the paper

```
366 \def\volumenumber#1{\def\currentvolume{#1}}
```

\issuenumber This sets the issue of the paper:

```
367 \def\issuenumber#1{\def\currentissue{#1}}
```

\publicationyear This sets the year of the paper

```
368 \def\publicationyear#1{\def\currentyear{#1}}
```

\papernumber This is absent from the `\issueinfo`.

```
369 \def\papernumber#1{\def\currentpaper{#1}}
370 \papernumber{0000}
```

\startpage This defines the starting page of the paper. We have some nice features to set up
roman page numbers for editorial stuff—probably not needed for this journal at
this time...

```
371 \def\startpage#1{\pagenumbering{arabic}\setcounter{page}{#1}%
372   \def\start@page{#1}%
373   \ifnum\c@page<\z@ \pagenumbering{roman}\setcounter{page}{-#1}%
374     \def\start@page{\romannumeral#1}%
375   \fi}
```

\endpage This macro again has a twist in it: if the argument is not set, it calculates the last
page number itself.

```
376 \def\endpage#1{\def\@tempa{#1}%
377   \ifx\@tempa\@empty\def\end@page{\pageref{LastPage}}%
378   \else\def\end@page{#1}\fi}
```

\pagespan This macro is different from the one provided by `amsart` because we want to have
the option of automatic calculation of the last page number.

```
379 \def\pagespan#1#2{\startpage{#1}\endpage{#2}}
380 \pagespan{1}{}
```

```

\g@addto@abstract Syntactic sugar around \g@addto@macro
381 \def\g@addto@abstract#1{\g@addto@macro{\@aom@abstract}{#1}}


\@getabstract Amsart typesets the abstract in a box. We preserve this peculiarity, but we need
to put abstract in a macro to output in the rpi file.
382 \long\def\@aom@abstract{}
383 \long\def\@getabstract#1{%
384   \bgroup
385     \ifx\languagename\undefined
386       \def\languagename{english}%
387     \fi
388     \g@addto@abstract{<begin abstract }%
389     \expandafter\g@addto@abstract\expandafter{\languagename}%
390     \g@addto@macro{\@aom@abstract{#1}}%
391     \g@addto@abstract{<end abstract }%
392     \expandafter\g@addto@abstract\expandafter{\languagename}%
393   \egroup
394   \ifx\maketitle\relax
395     \ClassWarning{aomart}{Abstract should precede
396       \protect\maketitle\space in AMS derived classes}%
397   \fi
398   \global\setbox\abstractbox=\vtop\bgroup%
399     \box\abstractbox
400     \vglue1pc%
401     \centering\normalfont\normalsize\bfseries\abstractname\par\vglue1pc}%
402     \list{}{\labelwidth\z@%
403       \leftmargin3pc \rightmargin\leftmargin%
404       \listparindent\normalparindent \itemindent\normalparindent%
405       \parsep\z@ \z@plus\p@%
406       \let\fullwidthdisplay\relax%
407     }%
408     \item[]\normalfont\Small#1
409   \endlist\egroup}

\abstract This puts abstract in a box and in a macro. Wasteful, but backward compatible
410 \renewenvironment{abstract}{\Collect@Body\@getabstract}{%
411   \ifx\@setabstract\relax\@setabstract\fi}

\proposed We do not typeset the name of the proposer
412 \let\proposed\@gobble

\seconded Or the seconder
413 \let\seconded\@gobble

\corresponding This is the corresponding author—again not typeset
414 \let\corresponding\@gobble

\version We do not typeset the current version of the manuscript either...
415 \let\version\@gobble

\doinumber Now databases' numbers of the article:
\mrnumber 416 \def\doinumber#1{\gdef\@doinumber{#1}}
\zblnumber 417 \doinumber{10.4007/annals.\currentyear.\currentvolume.\currentissue.\currentpaper}
\arxivnumber

```

```

418 \def\mrnumber#1{\gdef\@mrnumber{#1}}
419 \mrnumber{}
420 \def\zblnumber#1{\gdef\@zblnumber{#1}}
421 \zblnumber{}
422 \def\arxivnumber#1{\gdef\@arxivnumber{#1}}
423 \arxivnumber{}

```

`\copyrightyear` This is the copyright year in case it does not coincide with the publication year:

```

424 \def\copyrightyear#1{\def\@copyrightyear{#1}}
425 \copyrightyear{}

```

`\copyrightnote` This is the copyrightnote. The default has some trickery with the year:

```

426 \def\copyrightnote#1{\def\@copyrightnote{#1}}
427 \copyrightnote{\textcopyright~%
428   \ifx\@empty\@copyrightyear\currentyear\else\@copyrightyear\fi~%
429   Department of Mathematics, Princeton University}

```

3.9 Typesetting Top Matter

`\@mainrpi` We write the information about the paper into file.rpi (the The stream for the rpi file:

```

430 \newwrite\@mainrpi

```

`\aom@write@paper@info` This writes the information about the paper into the file `jobname.rpi`. Note that hyperref makes our life a little bit more complex

```

431 \def\@mainrpi{\aom@write@paper@info{%
432   \bgroup
433   \if@filesw
434     \openout\@mainrpi\jobname.rpi%
435     \def\and{\string\and\space}%
436     \ifx\r@LastPage\undefined
437       \edef\@tempa{\start@page}%
438     \else
439       \def\@tempc##1##2##3##4##5{##2}%
440       \edef\@tempa{\expandafter\@tempc\r@LastPage}%
441     \fi
442     \ifx\language\undefined
443       \def\language{english}%
444     \fi
445     \protected@write\@mainrpi{%
446       {\@percentchar authors=\authors}%
447       \protected@write\@mainrpi{%
448         {\@percentchar information={\@names}}%
449       \protected@write\@mainrpi{%
450         {\@percentchar title=\@title}%
451       \protected@write\@mainrpi{%
452         {\@percentchar year=\currentyear}%
453       \protected@write\@mainrpi{%
454         {\@percentchar volume=\currentvolume}%
455       \protected@write\@mainrpi{%
456         {\@percentchar issue=\currentissue}%
457       \protected@write\@mainrpi{%
458         {\@percentchar paper=\currentpaper}%

```

```

459  \protected@write\@mainrpi{%
460    {\@percentchar startpage=\start@page}%
461  \protected@write\@mainrpi{%
462    {\@percentchar endpage=\@tempa}%
463  \protected@write\@mainrpi{%
464    {\@percentchar doi=\@doinumber}%
465  \ifx\@zblnumber\empty\else
466  \protected@write\@mainrpi{%
467    {\@percentchar zbl=\@zblnumber}%
468  \fi
469  \ifx\@mrnumber\empty\else
470  \protected@write\@mainrpi{%
471    {\@percentchar mr=\@mrnumber}%
472  \fi
473  \ifx\@arxivnumber\empty\else
474  \protected@write\@mainrpi{%
475    {\@percentchar arxiv=\@arxivnumber}%
476  \fi
477  \protected@write\@mainrpi{%
478    {\@percentchar subjects=Primary \@primarysubjects; Secondary:
479      \@secondarysubjects}%
480  \protected@write\@mainrpi{%
481    {\@percentchar keywords=\@keywords}%
482  \protected@write\@mainrpi{%
483    {\@percentchar abstract=\@aom@abstract}%
484  \protected@write\@mainrpi{%
485    {\@percentchar articlrlanguage=\languagename}%
486  \AtEndDocument{\closeout\@mainrpi}%
487  \fi
488 \egroup}

```

\@maketitle@hook We add writing the information to the hook:

```
489 \def\@maketitle@hook{\aom@write@paper@info\global\let\@maketitle@hook\empty}
```

\@setttitle We do not uppercase title. Also, we use this occasion to set PDF information:

```

490 \def\@setttitle{\begin{center}%
491   \baselineskip20\p@\relax
492   \bfseries\LARGE
493   \title
494   \ifpdf
495     \hypersetup{pdftitle=\@title}%
496   \fi
497   \end{center}%
498 }

```

\@setauthors Now we typeset authors according to our specs. Again, we use this occasion to set some PDF information:

```

499 \def\@setauthors{%
500   \ifx\authors\empty\relax\else
501   \begingroup
502   \def\thanks{\protect\thanks@warning}%
503   \trivlist
504   \centering\footnotesize \topsep30\p@\relax
505   \advance\topsep by -\baselineskip

```

```

506   \item\relax
507   \def\@and{\{\upshape \!@\!om\!@nd\}\}%
508   \author\!andify\!authors
509   \ifpdf
510     \bgroup
511       \def\!om\!orcidlink##1{}%
512       \xdef\!tempa{\!authors}%
513     \egroup
514     \hypersetup{pdfauthor=\!tempa}%
515   \fi
516   \def\\{\protect\linebreak}%
517   \small \!@\!om\!@by{} \scshape\!authors\%
518   \!processcurrentcontribgroup
519   \ifx\!empty\!contribs
520     \else
521       ,\penalty-3 \space \!setcontribs
522   \fi
523   \endtrivlist
524   \endgroup
525 \fi}

```

\!setcontribs Contributors are set up in the same way as authors:

```

526 \def\!setcontribs{%
527   \def\!@and{\{\upshape \!@\!om\!@nd\}\}%
528   \author\!andify\!contribs
529   \!contribs
530 }

```

\!adminfootnotes We do not typeset keywords, so we change the definition:

```

531 \def\!adminfootnotes{%
532   \let\!makefnmark\relax \let\!thefnmark\relax
533   \ifx\!empty\!date\else \!footnotetext{\!setdate}\fi
534   \ifx\!empty\!subjclass\else \!footnotetext{\!setsubjclass}\fi
535   \ifx\!empty\!keywords\else \!setkeywords\fi
536   \ifx\!empty\!primarysubjects
537     \ifx\!empty\!secondarysubjects
538       \!setssubjects\fi
539     \!setssubjects\fi
540   \ifx\!empty\!thankses\else \!footnotetext{%
541     \def\!par{\!let\!par\!@par}\!setthanks}\%
542   \fi
543   \ifx\!empty\!copyrightnote\else \!footnotetext{%
544     \def\!par{\!let\!par\!@par}\!copyrightnote\!addpunct.}\%
545   \fi
546 }

```

\!setkeywords Typesetting keywords

```

547 \def\!setkeywords{%
548   \ifpdf
549     \hypersetup{pdfkeywords=\!keywords}%
550   \fi
551   \if\!om\!oldkeywords\else
552     \!footnotetext{Keywords: \!keywords}%
553   \fi

```

```

554 }

\@setsubjects Setting subjects
555 \def\@setsubjects{%
556   \let\@subjects\@empty
557   \ifx\@primarysubjects\@empty\else
558     \edef\@subjects{Primary:~\@primarysubjects}%
559   \fi
560   \ifx\@secondarysubjects\@empty\else
561     \ifx\@primarysubjects\@empty
562       \edef\@subjects{Secondary:~\@secondarysubjects}%
563     \else
564       \edef\@subjects{\@subjects; Secondary:~\@secondarysubjects}%
565     \fi
566   \fi
567   \ifpdf
568     \hypersetup{pdfsubject=\@subjects}%
569   \fi
570   \if@aom@oldkeywords\else
571     \@footnotetext{AMS Classification:~\@subjects.}%
572   \fi
573 }

```

\@and We want “and” in the footers to be lowercase. Since there is some uppercase involved, we protect it:

```
574 \def\@and{\MakeLowercase{\@aom@and}}
```

3.10 Typesetting End Matter

End matter is typeset at the end of the paper.

\enddoc@text This is the main macro for typesetting endmatter.

```

575 \def\enddoc@text{%
576   \ifx\@empty\@translators \else\@settranslators\fi
577   \ifx\@empty\@received \else\@setreceived\fi
578   \ifx\@empty\@revised \else\@setrevised\fi
579   \ifx\@empty\@addresses \else\@setaddresses\fi}

```

\@setreceived A bunch of macros for setting centered dates

```
\@setrevised 580 \def\@setreceived{{\centering(Received: \@received)\par}}
```

```
\@setaccepted 581 \def\@setrevised{{\centering(Revised: \@revised)\par}}
```

```
\@setpublished 582 \def\@setaccepted{{\centering(Accepted: \@accepted)\par}}
```

```
\@setpublishedonline 583 \def\@setpublished{{\centering(Published: \@published)\par}}
```

```
584 \def\@setpublishedonline{{\centering(Published online: \@publishedonline)\par}}
```

\emailaddrname We do not want the word “address” here:

```
585 \def\emailaddrname{\itshape E-mail}
```

\@setaddresses The difference between our definition and the one in `amsart` is that we want the e-mail and URL to be clickable

```

586 \def\@setaddresses{\par
587   \nobreak \begingroup
588   \footnotesize
```

```

589 \def\author##1{\goodbreak\addvspace\bigskipamount{\scshape##1\par\nobreak}%%
590 \def\\{\unskip, \ignorespaces}%
591 \interlinepenalty\@M
592 \def\address##1##2{\begingroup\nobreak
593   \par\hangindent=22pt\hangafter=0\parindent=0pt
594   \@ifnotempty{##1}{(\ignorespaces##1\unskip) }%
595   {\ignorespaces##2}\par\endgroup}%
596 \def\curraddr##1##2{\begingroup
597   \@ifnotempty{##2}{\nobreak\indent\curraddrname
598     \@ifnotempty{##1}{, \ignorespaces\scshape##1\unskip}\hspace{0.2em}: \space
599     ##2\par}\endgroup}%
600 \def\email##1##2{\begingroup
601   \@ifnotempty{##2}{\nobreak\indent\emailaddrname
602     \@ifnotempty{##1}{, \ignorespaces\#1\unskip}\hspace{0.2em}: \space
603     \href{mailto:##2}{\nolinkurl{##2}}\par\nobreak}\endgroup}%
604 \def\urladdr##1##2{\begingroup
605   \@ifnotempty{##2}{\nobreak\indent
606     \@ifnotempty{##1}{, \ignorespaces\#1\unskip}%
607     \url{##2}\par\nobreak}\endgroup}%
608 \def\orcid##1{\begingroup
609   \@ifnotempty{##1}{\nobreak\indent
610     \url{https://orcid.org/##1}\par\nobreak}\endgroup}%
611 \addresses
612 \endgroup
613 }

```

3.11 Sectioning

\contentsnamefont This is the font for the word “Contents”:

```
614 \renewcommand\contentsnamefont{\bfseries}
```

\section We want our sections to be centered and bold:

```

615 \def\section{\@startsection{section}{1}%
616   \z@\linespacing\@plus\linespacing\@.5\linespacing\%%
617   {\normalfont\bfseries\centering}}

```

\subsection We want our subsections to be indented and italic:

```

618 \def\subsection{\@startsection{subsection}{2}%
619   {\parindent}.5\linespacing\@-.5em\%%
620   {\normalfont\itshape}}

```

\oldsubsections This macro restores the values for \subsection spacing prior to v1.1.

```

621 \def\oldsubsections{%
622 \gdef\subsection{\@startsection{subsection}{2}%
623   {\parindent}.5\linespacing\@plus.7\linespacing\@-.5em\%%
624   {\normalfont\itshape}}}

```

\subsubsection Subsubsections are formatted exactly like subsections:

```

625 \def\subsubsection{\@startsection{subsubsection}{3}%
626   {\parindent}.5\linespacing\@-.5em\%%
627   {\normalfont\itshape}}

```

\Hy@AlphNoErr The newer (circa 2012) hyperref defines this command. However, older versions do not. Here we provide it:

```
628 \providecommand\Hy@AlphNoErr[1]{%
629   \ifnum\value{#1}>26 %
630     \Alph\number\value{#1}%
631   \else
632     \ifnum\value{#1}<1 %
633       \Alph\number\value{#1}%
634     \else
635       \Alph{#1}%
636     \fi
637   \fi
638 }%
```

\appendix We redefine appendix to ensure the letter in section number is always upright:

```
639 \def\appendix{\par\c@section\z@ \c@subsection\z@
640   \gdef\theHsection{\Hy@AlphNoErr{section}}%
641   \let\sectionname\appendixname
642   \def\thesection{\upshape@\Alph\c@section}}
```

3.12 Figures and Tables

\@captionheadfont This is the font for the words “Figure” or “Table” in captions. Unlike amsmath with is small caps, we want just plain Roman font:

```
643 \def\@captionheadfont{\normalfont}
```

3.13 Theorems

Here we redefine three main style of amsart. Here are the arguments of \newtheoremstyle from [3]:

```
#1
\newtheoremstyle{NAME}{%
  #2           #3           #4
  {ABOVESPACE}{BELOWSPACE}{BODYFONT}{%
    #5           #6           #7           #8
    {INDENT}{HEADFONT}{HEADPUNCT}{HEADSPACE}{%
      #9
      {CUSTOM-HEAD-SPEC}}}
```

In the *plain* style the name (“theorem”) is in small caps, the number is in normal font, the optional note is also in normal font, and the text is italics.

```
644 \newtheoremstyle{plain}{0.5\linespacing}{0.5\linespacing}{\sishape}{%
645   {\parindent}{\scshape}{.}{0.5em}{%
646     {\thmname{#1}\thmnumber{ #2}\thmnote{\normalfont{} (#3)}}}}
```

In the *definition* style the name is italics, and the body font is upright:

```
647 \newtheoremstyle{definition}{0.5\linespacing}{0.5\linespacing}{\upshape}{%
648   {\upshape}{\parindent}{%
649     {\sishape}{.}{0.5em}{%
650       {\thmname{#1}\thmnumber{ #2}\thmnote{\normalfont{} (#3)}}}}}
```

In our class there is no difference between `remark` and `definition` theorem styles:

```
651 \newtheoremstyle{remark}{0.5\linespacing}{0.5\linespacing}%
652   {\upshape}{\parindent}%
653   {\sishape}{.}{0.5em}%
654   {\thmname{\#1}\thmnumber{\ #2}\thmnote{\normalfont{} (\#3)}}%
```

`\newtheorem` For compatibility reasons we need to accept `\newtheorem` with optional first argument—and silently drop it. The problem is, there is `\newtheorem*`, so we need to check which one we deal with... The command `\@xnthm` here is from `amsthm`; it does the real work with the real parameters.

```
655 \renewcommand{\newtheorem}{\@ifstar{\@aom@newthm@star}{\@aom@newthm}}
656 \def\@aom@newthm@star{\@ifnextchar[{\@aom@newthm@star@}{\@aom@newthm@star@[]}}
657 \def\@aom@newthm{\@ifnextchar[{\@aom@newthm@}{\@aom@newthm@[]}}
658 \def\@aom@newthm@star@[#1]{\@xnthm *}
659 \def\@aom@newthm@[#1]{\@xnthm \relax}
```

`proof` We want our proofs to be indented:

```
660 \renewenvironment{proof}[1][\proofname]{\par
661   \pushQED{\qed}%
662   \normalfont \topsep6\p@\oplus6\p@\relax
663   \trivlist
664   \item[\hspace{\labelsep}\hspace{\parindent}
665     \itshape
666     #1\@addpunct{.}]\ignorespaces
667 }{%
668   \popQED\endtrivlist\endpfalse
669 }
```

3.14 Bibliography Macros

`\repeatedauthors` When the authors are repeated, we used change them to `\bysame`; we no more do this:

```
670 \def\repeatedauthors#1{\ClassWarning{aomart}{The command is obsolete}#1}
```

`\bysame` We no longer use `\bysame`

```
671 \let\bysame@orig=\bysame
672 \def\bysame{\ClassWarning{aomart}{We no longer omit
673   repeated authors}\bysame@orig}
```

`\doi` Typesetting doi...

```
674 \def\doi#1{%
675   \if@aom@doiMMXVI
676     \url{http://dx.doi.org/#1}%
677   \else
678     \if@aom@olddoi
679       \href{http://dx.doi.org/#1}{doi: \path{#1}}%
680     \else
681       \url{https://doi.org/#1}%
682     \fi
683   \fi}
```

```

\mr Typesetting urls
\zbl 684 \def\mr#1{\href{http://www.ams.org/mathscinet-getitem?mr=#1}{MR~\path{#1}}}
\arxiv 685 \def\zbl#1{\href{http://www.zentralblatt-math.org/zmath/en/search/?q=an:#1}{Zbl~\path{#1}}}
\jfm 686 \def\arxiv#1{\href{http://www.arxiv.org/abs/#1}{arXiv~\path{#1}}}
687 \def\jfm#1{\href{http://www.emis.de/cgi-bin/JFM-item?#1}{JFM~\path{#1}}}

\bibliofont We make this \small rather than \Small in amsart
688 \renewcommand{\bibliofont}{\small}

```

3.15 Additional Macros

\EditorialComment This macro is noop in normal mode, but is a tiny marginpar in the manuscript mode

```

689 \newcommand{\EditorialComment}[2][default]{\if@aom@manuscript@mode\begin{group}
690   \expandafter\ifx\csname EditorialComment@\#1\endcsname\relax
691     \else
692       \marginparwidth=75pt\marginpar{\scriptsize\raggedright#2}\fi
693   \egroup
694 \fi}

```

\ECSelect

```

695 \def\ECSelect#1{\if@aom@manuscript@mode
696   \@for\EC@level:=#1\do{%
697     \expandafter\gdef\csname
698       EditorialComment@\EC@level\endcsname{\EditorialComment}%
699   \fi}
700 \AtBeginDocument{\ECSelect{default}}

```

\Highlight

```

701 \newcommand{\Highlight}[2][default]{%
702   \expandafter\ifx\csname Highlight@\#1\endcsname\relax
703   #2\else
704   \csname Highlight@\#1\endcsname{#2}\fi}

```

\HSelect

```

705 \newcommand{\HSelect}[2][magenta]{\if@aom@manuscript@mode
706   \@for\TC@level:=#2\do{\expandafter
707     \gdef\csname Highlight@\TC@level\endcsname##1{\begin{group}
708       \Hy@colorlinksfalse
709       \def\Hy@colorlink##1{\begingroup}%
710       \def\Hy@endcolorlink{\endgroup}%
711       \color{#1}##1\egroup}##
712   \fi}
713 \AtBeginDocument{\HSelect{default}}

```

\@fullref This macro creates a wide link for the reference. It has four parameters: the word (theorem, equation, . . .), the “pre” punctuation, the reference and the “post” punctuation.

```

714 \def\@fullref#1#2#3#4{\hyperref[#3]{#1~#2\ref*{#3}#4}}

```

\fullref A reference without parentheses:

```

715 \newcommand{\fullref}[2]{\@fullref{#1}{#2}}

```

```

\pfullref A reference with parentheses:
716 \newcommand{\pfullref}[2]{\@fullref{\#1}{()}{\#2}{}}}

\bfullref A reference with brackets:
717 \newcommand{\bfullref}[2]{\@fullref{\#1}{[]}{\#2}{[]}}}

\eqfullref Here we do not use the standard common \@fullref because we want \eqref to
work...
718 \newcommand{\eqfullref}[2]{\hyperref[#2]{\#1^{\textup{\tagform@\{ref*\#2\}}}}}

\fullpageref A wide link for page reference. Note that the word “page” can be omitted
719 \newcommand{\fullpageref}[2][page]{\hyperref[#2]{\#1^{\pageref*\#2}}}

\eqnarray While we do not recommend the use of \eqnarray, we still would like to correct
the ugly spacing around it...
720 \def\eqnarray{%
721   \stepcounter{equation}%
722   \def\@currentlabel{\p@equation\theequation}%
723   \global\@eqnswtrue
724   \m@th
725   \global\@eqcnt\z@
726   \tabskip\@centering
727   \let\\@eqncr
728   $$\arraycolsep\p@
729   \everycr{}\halign to\displaywidth\bgroup
730     \hskip\@centering$\displaystyle\tabskip\z@skip\#\$\@eqnsel
731     &\global\@eqcnt\@ne\hskip \tw@\arraycolsep \hfil\#\$\hfil
732     &\global\@eqcnt\tw@\hskip \tw@\arraycolsep
733     $\displaystyle\#\$\hfil\tabskip\@centering
734     &\global\@eqcnt\thr@@ \hb@xt@\z@\bgroup\hss##\egroup
735     \tabskip\z@skip
736   \cr
737 }

\includecolorgraphics Color graphics: select either the first or the second argument.
738 \newcommand\includecolorgraphics[3][]{\if@ao@screen@mode
739   \includegraphics[#1]{#2}\else
740   \includegraphics[#1]{#3}\fi}

\funding The macro to print grants. It adds to the rpi file the information about grants
741 \newcommand\funding[3][]{%
742   \protected@write\@mainrpif{}%
743   {\@percentchar sponsor=\#2, grantid=\#3}%
744   \def\@tempa{\#1}\relax%
745   \ifx\@tempa\empty\relax
746     \def\@tempb{\#3}%
747     \#2%
748     \ifx\@tempb\empty\relax\else\ (grant~\#3)\fi
749   \else
750     \#1
751   \fi}

```

3.16 End of Class

752 ⟨/class⟩

References

- [1] George Grätzer. *Math into L^AT_EX*. Birkhäuser, Boston, third edition, 2000.
- [2] UK T_EX Users Group. UK list of T_EX frequently asked questions. <http://www.tex.ac.uk/cgi-bin/texfaq2html>, 2008.
- [3] Michael Downes and Barbara Beeton. *The amsart, amsproc, and amsbook document classes*. American Mathematical Society, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes>.
- [4] Sebastian Rahtz and Heiko Oberdiek. *Hypertext Marks in L^AT_EX: a Manual for Hyperref*, September 2006. <http://mirrors.ctan.org/macros/latex/contrib/hyperref>.
- [5] Heiko Oberdiek. *The ifpdf Package*, February 2006. <http://mirrors.ctan.org/macros/latex/contrib/oberdiek>.
- [6] Piet van Oostrum. *Page Layout in L^AT_EX*, March 2004. <http://mirrors.ctan.org/macros/latex/contrib/fancyhdr>.
- [7] Sergei V. Znamenskii. *Unslanted Punctuation in Computer Modern Italic*, January 2003. <http://mirrors.ctan.org/fonts/cm/cmtiup>.
- [8] Yannis Haralambous. *My Humble Additions to (La)T_EX Mathematics*, January 1996. <http://mirrors.ctan.org/macros/latex/contrib/yhmath>.
- [9] American Mathematical Society. *User's Guide for the amsmath Package (Version 2.0)*, February 2002. <http://mirrors.ctan.org/macros/latex/required/amslatex/math/amsldoc.pdf>.
- [10] Johannes Braams. *Babel, a Multilingual Package For Use With L^AT_EX's Standard Document Classes*, April 2005. <http://mirrors.ctan.org/macros/latex/required/babel>.
- [11] American Mathematical Society. *Instructions for Preparation of Papers and Monographs, AMSE^AT_EX*, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/instr-1.pdf>.
- [12] American Mathematical Society. *Using the amsthm Package*, August 2004. <http://mirrors.ctan.org/macros/latex/required/amslatex/classes/amsthdoc.pdf>.
- [13] Michel Goossens, Sebastian Rahtz, and Frank Mittelbach. *The L^AT_EX Graphics Companion: Illustrating Documents With T_EX and PostScript*. Addison-Wesley Series on Tools and Techniques for Computer Typesetting. Addison-Wesley, Reading, Ma., 1997.
- [14] Leo Stein. *The orcidlink package*.

Change History

v0.10	Made remark theorem style identical to definition theorem style 32
	Documentation update 2
	Screen mode triggers special URL settings 16
	\if@aom@screen@mode: Added screen mode 14
	\jfm: Added macro 33
v0.2	\@fullref: Added macro 33
	General: First fully functional version 2
v0.3	\@setaddresses: Deleted the word URL 29
	E-mail is now in Roman font 29
	\@setpublishedonline: Decreased font 29
	\@typesizes: Corrected typo in the definition of Small 17
	Increased LARGE from 16 pt to 17 pt 17
	\bfullref: Added macro 34
	\emailaddrname: Changed macro 29
	\eqfullref: Added macro 34
	\fullref: Added macro 33
	\pfullref: Added macro 34
	\proof: Redefined macro 32
	\subsection: Redefined macro 30
v0.6	General: Changes to bst files 2
	Fullref.pl is much less aggressive now 2
	\@setauthors: 'By' and 'and' are in Roman font now 27
	\belowdisplayskip: Changed belowdisplayskip 18
	\biblio: Changed default 33
	\zbl: Changed capitalization 33
v0.7	General: Bibliography styles changed 2
v0.8	General: Added yhmath 17
	Bibliography styles update 2
	Changed authors in header 19
	Documentation update 2
	Switched to cmtiup 17
	\specialdigits: Redefined to noop 17
v0.9	General: Bibliography styles update 2
	Changed font for the folio on the first page 19
	Documentation update 2
	\@and: Redefined macro 29
v0.4	General: Changed definition theorem style 31
	Changed plain theorem style 31
	Deleted lineno package dependence 16
	Deleted remark theorem style 32
	Documentation update 2
	Switched to upright digits in italics everywhere 17
	Used line numbers for headings 19
	\@aom@linecount: Added macro 19
	\enddoc@text: Deleted many dates 29
v0.5	General: Added extra footer in manuscript mode 19
	Corrected the byg with math in headers 19

\@setaddresses:	Deleted spurious space in urladdress	29	\aom@write@paper@info:	Added macro	26	
\@setpublishedonline:	Increased font	29	v1.14a	\annalsurl:	New url	20
\abstract:	Added parindent for the first par	25	v1.15	\doi:	Doi according to the new Crossref recommendations . . .	32
\eqnarray:	Redefined standard macro	34	\if@aom@doiMMXVI:	Added another options	15	
v1.0	General: Top matter macros are now only in preamble	2	v1.16	General: We require environ package	16	
	\doinumber:	Added default	\aom@write@paper@info:	Added names, abstract, subjects, keywords, zblnumber, arxivnumber	26	
	\papernumber:	Added macro	\arxivnumber:	Added macro	25	
v1.1	General: In manuscript mode the links are always blue	16	\author:	Redefined amsart definition	21	
v1.10	\@and:	Added internationalization	\abstract:	Redefined using environ	25	
	\@aom@and:	Added macro	\email:	Redefined amsart definition	22	
	\@aom@by:	Added macro	\fulladdress:	Redefined	21	
	\@setauthors:	Internationalization	\givenname:	Redefined	21	
	\doi:	Introduced the logic for old doi formatting	\surname:	Redefined	21	
	\if@aom@olddoi:	Added old DOI processing	\urladdr:	Redefined amsart definition	23	
v1.11	General: Added \fulladdress	2	v1.17	General: Added new field totalpages to the bibliography	2	
	Added new commands for copyright statement	2	v1.17a	General: Bug fixed in aomplain.bst	2	
	Bibliography change: titlenote, deleted bysame	2	v1.18	General: New option <code>oldkeywords</code> and printing keywords and subjects by default	2	
	Deleted \repeatedauthors from the documentation	2	\@setaddresses:	Added orcid	29	
	\@adminfootnotes:	Added copyright statement	\@setkeywords:	Now we print keywords	28	
	\@setaddresses:	Changed email handling	\@setssubjects:	Now we print subjects	29	
	\bysame:	Made the macro obsolete	\if@aom@oldkeywords:	Added keywords processing	15	
	\copyrightnote:	Added macro	\orcid:	Added macro	23	
	\copyrightyear:	Added macro	\subject:	Drop scheme and primary/secondary	23	
	\fulladdress:	Added macro	v1.19	General: Bibliography changes	2	
	\repeatedauthors:	Now this command is obsolete	v1.2	General: Bibliography styles update	2	
v1.12	\appendix:	Added hyperref definition	\@setaddresses:	Changed font for current address	29	
v1.13	\Hy@AlphaNoErr:	Added macro for older installations				
v1.14	\@mainrpi:	Added macro				
	\@maketitle@hook:	Added macro				

\arxiv:	Now we properly treat numbers with underscores . . .	33	\contribs:	Introduced macro	21	
\doi:	Now we properly treat numbers with underscores . . .	32	\if@startcontribgroup:	Introduced macro	21	
\jfm:	Now we properly treat numbers with underscores . . .	33	v1.27			
\mr:	Now we properly treat numbers with underscores . . .	33	\aom@write@paper@info:	Keep the .rpi file open till the end of document	26	
\oldsubsections:	Introduced macro	30	\funding:	Added macro	34	
\subsection:	Decreased vertical spacing	30	v1.28			
\zbl:	Now we properly treat numbers with underscores . . .	33	\@setauthors:	Added treatment of orcid	27	
v1.20			\aom@current@orcid@target:	Added macro	23	
\@adminfootnotes:	Make primary and secondary subjects separated	28	\aom@orcidlink:	Added macro	23	
\@setssubjects:	Make primary and secondary subjects separated .	29	\contrib:	Added typesetting orcid	22	
\aom@write@paper@info:	Make primary and secondary subjects separated	26	\orcid:	Added typesetting orcid	23	
\subject:	Make primary and secondary subjects separated .	23	v1.29			
v1.21			\@setaddresses:	Reformatted	29	
\@getabstract:	Added multilanguage abstracts	25	v1.3	General: Corrected bug with doinumber	19	
\aom@write@paper@info:	Added main language	26	v1.30	\@citex:	Redefined macro	15
\g@addto@abstract:	Added macro	25	\@makefnmark:	Use kernel version of footnote marks	15	
v1.22			\@makefnmark@kernel:	Use kernel version of footnote marks	15	
General:	In screen mode we no longer crop pages	16	v1.31	\@setaddresses:	Reformatted	29
v1.23			v1.32	\@citex:	Added ‘and’ and oxford comma	15
General:	Made ymath large symbols default	17	\ECSelect:	Added macro	33	
\widetilde:	We are taking wide hat and wide tilde from amsfonts	17	\EditorialComment:	Rewrote macro, adding levels	33	
v1.24			\Highlight:	Added macro	33	
\if@aom@printscheme:	Added optional printing of scheme	15	\HSelect:	Added macro	33	
\subject:	Added scheme	23	\includecolorgraphics:	Added macro	34	
v1.25			v1.33	\@setaddresses:	No break after author name	29
\fullpageref:	Added macro	34	v1.4	General:	Deleted noamsfonts option	15
v1.26			\subsection:	Deleted stretch in vertical spacing	30	
\@currentcontribution:	Introduced macro	21	\subsubsection:	Introduced the macro	30	
\@currentcontributors:	Introduced macro	21	v1.5	General:	Added noopsort to the styles, corrected typo	2
\@processcurrentcontribgroup:	Introduced macro	22			Added sortyear to the styles	2
\contrib:	Redefined amsart macro	22				

\arxiv: Typo corrected	33	v1.9	
v1.6		\doi: Changed doi look	32
General: Bibliography change:		v2.28	
aomalpha now respects key		\headheight: Increased	19
field in the bib file	2	v2.30	
\appendix: Redefined the macro .	31	General: Changed the margins for	
v1.7		enumerate	18
General: Suppressed page number		v2.32	
in the header for one-page		\itemize: Changed the margins	
articles	19	for itemize	18

Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\@and	276, 507, 527, <u>574</u>
\@Alph	642
\@M	591
\@accepted	360, 361, 582
\@addpunct	544, 666
\@adminfootnotes	<u>531</u>
\@annalsurl	192, 207
\@aom@abstract	381, 382, 390, 483
\@aom@and	97, 99, 100, 101, 276, 507, 527, 574
\@aom@by	96, 99, 100, 101, 517
\@aom@doiMMXVIfalse	42
\@aom@doiMMXVIttrue	43
\@aom@linecount	162, 176, 179, 188
\@aom@manuscript@modefalse	33
\@aom@manuscript@modetrue	34
\@aom@newthm	655, 657
\@aom@newthm@	657, 659
\@aom@newthm@star	655, 656
\@aom@newthm@star@	656, 658
\@aom@olddoifalse	39
\@aom@olddoittrue	40
\@aom@oldkeywordsfalse	45
\@aom@oldkeywordstrue	46
\@aom@printschemefalse	48
\@aom@printschemetrue	49
\@aom@screen@modefalse	36
\@aom@screen@modetrue	37
\@arxivnumber	422, 473, 475
\@auxout	76
\@captionheadfont	<u>643</u>
\@centering	726, 730, 733
\@cite	65
\@cite@ofmt	81
\@citea	64, 66, 70, 72
\@citeb	62, 65, 75, 76, 77, 80, 81
\@citex	<u>60</u>
\@copyrightnote	426, 543, 544
\@copyrightyear	424, 428
\@currentcontribution	269, 282, 293, 301, 306, 314
\@currentcontributors	270, 275, 277, 285, 290, 307, 309
\@currentlabel	722
\@date	533
\@dblarg	267
\@doinumber	203, 204, 205, 416, 464
\@empty	64, 75, 203, 250, 259, 275, 278, 292, 293, 333, 335, 336, 337, 338, 340, 357, 359, 361, 363, 365, 377, 428, 465, 469, 473, 489, 500, 519, 533, 534, 535, 536, 537, 540, 543, 556, 557, 560, 561, 576, 577, 578, 579, 745, 748
\@endformatdate	349, 350
\@endpefalse	668
\@eqcnt	725, 731, 732, 734
\@eqnccr	727
\@eqnsel	730
\@eqnswtrue	723
\@firstofone	75
\@footnotetext	533, 534,
\@for	62, 65, 696, 706
\@formatdate	<u>349, 350</u>
\@fullref	. <u>714</u> , 715, 716, 717
\@getabstract	. <u>382</u> , 410
\@gobble	412, 413, 414, 415
\@ifnextchar	656, 657
\@ifnotempty	258, 594, 597, 598, 601, 602, 605, 606, 609
\@ifpackageloaded	98
\@ifstar	655
\@ifundefined	77
\@itemdepth	148, 149, 150
\@itemitem	150, 151
\@ixpt	120
\@keywords	333, 334, 481, 535, 549, 552
\@latex@warning	79
\@listi	146
\@mainrpi	430, 434, 445, 447, 449, 451, 453, 455, 457, 459, 461, 463, 466, 470, 474, 477, 480, 482, 484, 486, 742
\@makefnmar	<u>59</u>
\@makefnmark	57, 59, 532
\@makefnmark@kernel	57, 59
\@maketitle@hook	<u>489</u>
\@mathmeasure	104, 108
\@mrnumber	418, 469, 471
\@names	245, 246, 247, 248, 252, 255, 311, 312, 314, 315, 320, 324, 329, 448
\@ne	149, 165, 167, 731
\@nx	267, 268
\@onlypreamble	209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228,

229, 230, 231,
 232, 233, 234,
 235, 236, 237,
 238, 239, 240,
 241, 242, 243, 244
`\@par` 541, 544
`\@percentchar`
 446, 448,
 450, 452, 454,
 456, 458, 460,
 462, 464, 467,
 471, 475, 478,
 481, 483, 485, 743
`\@plus` 405, 616, 623, 662
`\@primaryscheme` ... 337
`\@primarysubjects` ...
 335, 478,
 536, 557, 558, 561
`\@processcurrentcontribgroup`
 274, 305, 518
`\@published` 362, 363, 583
`\@publishedonline` ...
 364, 365, 584
`\@received`
 356, 357, 577, 580
`\@revised`
 358, 359, 578, 581
`\@secondaryschme` ... 338
`\@secondarysubjects` ...
 336, 479,
 537, 560, 562, 564
`\@setabstract` 411
`\@setabstracta` 411
`\@setaccepted` 580
`\@setaddresses` 579, 586
`\@setauthors` 499
`\@setcontribs` .. 521, 526
`\@setdate` 533
`\@setkeywords` .. 535, 547
`\@setpublished` 580
`\@setpublishedonline` 580
`\@setreceived` .. 577, 580
`\@setrevised` .. 578, 580
`\@setsubjclass` 534
`\@setssubjects`
 538, 539, 555
`\@setthanks` 541
`\@setttitle` 490
`\@settranslators` .. 576
`\@startcontribgroupfalse` ..
 273, 298, 302
`\@startcontribgrouptrue` ..
 291

`\@startsection`
 615, 618, 622, 625
`\@subjclass` 534
`\@subjects` 556, 558,
 562, 564, 568, 571
`\@tempa` ... 289, 292,
 301, 376, 377,
 437, 440, 462,
 512, 514, 744, 745
`\@tempb` 746, 748
`\@tempc` 439, 440
`\@tempcnta` 61,
 62, 68, 69, 165,
 166, 167, 351, 355
`\@tempcntb` .. 63, 67, 68
`\@thefnmark` 532
`\@title` ... 450, 493, 495
`\@toodeep` 148
`\@topsep` 504, 505
`\@translators` 576
`\@typesizes` 119
`\@undefined` 436
`\@viiipt` 120
`\@viipt` 120
`\@vipt` 120
`\@xiipt` 123
`\@xipt` 122
`\@xnthm` 658, 659
`\@xp` 268
`\@xpt` 121
`\@xviiipt` 123
`\@zblnumber` 420, 465, 467
`\`` 166, 202, 516, 590, 727
`\lrcorner` 748
`\lrcorner 10pt (option)` 4
`\lrcorner 11pt (option)` 4
`\lrcorner 12pt (option)` 4
`\lrcorner 8pt (option)` 4
`\lrcorner 9pt (option)` 4

A

`\abovedisplayskip` .. 131
`\abstract` 410
`\abstract` (env.) 6
`\abstractbox` .. 398, 399
`\abstractname` 401
`\accepted` .. 7, 225, 356
`\address` ... 5, 213, 592
`\addresses`
 265, 316, 319,
 323, 328, 579, 611
`\addto` 99, 100, 101
`\addvspace` 589

B

`\baselineskip`
 125, 491, 505
`\begin` 19,
 175, 178, 187, 490
`\begingroup` ... 501,
 587, 592, 596,
 600, 604, 608, 709
`\belowdisplayskip` .. 131
`\bfseries` 77,
 401, 492, 614, 617
`\bfullref` 9, 717
`\bgroup` 384,
 398, 432, 510,
 689, 707, 729, 734
`\biblio` 688
`\bigskipamount` 589
`\box` 399
`\bysame` 671
`\bysame@orig` .. 671, 673

C

`\c@page` 373

```

\c@section . . . 639, 642 \DeclareSymbolFont . 103 \edef . . . . . 75, 150,
\c@subsection . . . . 639 \def . . . . . 24, 60, 196, 198, 200,
\captionsenglish . . 101 66, 70, 72, 96, 204, 267, 437,
\captionsfrench . . 99 97, 99, 100, 101, 440, 558, 562, 564
\captionsgerman . . 100 116, 119, 153, \editor . . . . . 7, 231
\centering . . . . . 401, 195, 207, 245, \EditorialComment .
504, 580, 581, 246, 247, 248, . . . . . 8, 689, 698
582, 583, 584, 617 269, 270, 271, \egroup 393, 409, 488,
\cfoot . . . . . 206 274, 276, 289, 513, 693, 711, 734
\chead . . . . . 191 326, 333, 339, \else 71, 87, 90, 107,
\citation . . . . . 76 349, 350, 356, 111, 149, 199,
\ClassError . . . . . 294 358, 360, 362, 202, 203, 253,
\ClassInfo . . . . . 52, 54 364, 366, 367, 261, 275, 278,
\ClassWarning . . . . . 25, 368, 369, 371, 297, 308, 333,
114, 395, 670, 672 372, 374, 376, 342, 378, 428,
\closeout . . . . . 486 377, 378, 379, 438, 465, 469,
\clubpenalty . . . . . 139 381, 382, 383, 473, 500, 520,
\CodeIndex . . . . . 16 386, 416, 418, 533, 534, 535,
\Collect@Body . . . . . 410 420, 422, 424, 538, 539, 540,
\color . . . . . 711 426, 431, 435, 543, 551, 557,
\contentsnamefont . . 614 439, 443, 489, 560, 563, 570,
\contrib . . . . . 5, 211, 288 490, 499, 502, 576, 577, 578,
\contribs . . . . . 271, 278, 507, 511, 516, 579, 631, 634,
279, 281, 283, 526, 527, 531, 677, 680, 691,
284, 519, 528, 529 541, 544, 547, 703, 739, 748, 749
\copyrightnote . . . . . 6, 236, 426 555, 574, 575, \email . . . 5, 212, 318, 600
\copyrightyear . . . . . 7, 424 580, 581, 582, \emailaddrname 585, 601
\copyrighyear . . . . . 237 583, 584, 585, \EnableCrossrefs . . . 18
\corresponding . . . . . 7, 230, 414 586, 589, 590, \end 21, 177, 180, 189, 497
\cr . . . . . 736 592, 596, 600, \end@page . . . . . 197,
\csname . . . . . 81, 151, 604, 608, 615, 200, 202, 377, 378
268, 340, 341, \endcsname . . . 81, 151,
343, 346, 690, 268, 340, 341,
697, 702, 704, 707 639, 642, 643, 343, 346, 690,
656, 657, 658, 698, 702, 704, 707
\curraddr . . . . . 5, 214, 596 659, 670, 672, \endddoc@text . . . . . 575
\curraddrname . . . . . 597 674, 684, 685, \endgroup . . . . . 524,
\currentissue . . . . . 367, 417, 456 686, 687, 695, 595, 599, 603,
\CurrentOption . . . . . 27, 607, 610, 612, 710
28, 29, 30, 31, 50 \dimen . . . . . 135 \endlist . . . . . 156, 409
\currentpaper . . . . . 369, 417, 458 \displaystyle . . . . . 730, 733 \endpage . . . . . 7, 240, 376, 379
\currentvolume . . . . . 192, 366, 417, 454 \displaywidth . . . . . 729 \endtrivlist . . . . . 523, 668
\currentyear . . . . . 193, environments:
368, 417, 428, 452 \do . . . . . 62, 65, 696, 706 abstract . . . . . 6
\endlist . . . . . 156, 409
\endpage . . . . . 7, 240, 376, 379
\endtrivlist . . . . . 523, 668
environments:
abstract . . . . . 6
eqnarray . . . . . 9
eqnarray* . . . . . 9
\eqfullref . . . . . 9, 718
\eqnarray . . . . . 720
eqnarray (env.) . . . . . 9
eqnarray* (env.) . . . . . 9
\evensidemargin . . . . . 129
\everycr . . . . . 729
\expandafter . . . . . 75,
205, 281, 282,

```

284, 285, 313,	248, 252, 254,	\if@aom@olddoi . 38, 678
314, 330, 340,	255, 262, 265,	\if@aom@oldkeywords
341, 343, 346,	279, 281, 283, 44, 551, 570
389, 392, 440,	284, 309, 311,	\if@aom@printscheme
690, 697, 702, 706	312, 313, 315, 47, 345
	316, 319, 320,	\if@aom@screen@mode
F	323, 324, 328, 35, 84, 738
\fancyfoot ... 171, 181	329, 330, 334,	\if@filesw 76, 433
\fancyhead 170, 172,	343, 346, 381, 390	\if@startcontribgroup
173, 175, 178, 183	\G@refundefinedtrue 78 272, 304
\fancyhf 185	\gdef 207,	\ifcase
\fancypagestyle ... 184	251, 257, 260,	105, 109
\fi .. 73, 74, 76, 93,	290, 306, 307,	\IfFileExists 112
107, 111, 154,	333, 341, 416,	\ifnum .. 68, 69, 148,
168, 182, 190,	418, 420, 422,	167, 373, 629, 632
201, 202, 205,	622, 640, 697, 707	\ifpdf 494, 509, 548, 567
256, 263, 280,	\givenname .. 5, 217, 245	\ifx 197, 202,
286, 299, 300,	\global 398, 489, 723,	203, 250, 259,
303, 310, 334,	725, 731, 732, 734	275, 278, 292,
344, 348, 354,	\goodbreak 589	293, 301, 333,
375, 378, 387,		340, 377, 385,
397, 411, 428,	H	394, 411, 428,
441, 444, 468,	\halign 729	436, 442, 465,
472, 476, 487,	\hangafter 593	469, 473, 500,
496, 515, 522,	\hangindent 593	519, 533, 534,
525, 533, 534,	\hb@xt@ 734	535, 536, 537,
535, 538, 539,	\hbox 77	540, 543, 557,
542, 545, 550,	\headheight 159	560, 561, 576,
553, 559, 565,	\headrulewidth 160	577, 578, 579,
566, 569, 572,	\headsep 158	690, 702, 745, 748
576, 577, 578,	\hexnumber@ ... 106, 110	\ignorespaces
579, 636, 637,	\hfil 731, 733	. 590, 594, 595,
682, 683, 692,	\Highlight 8, 701	598, 602, 606, 666
694, 699, 704,	\href 192,	\immediate 76
712, 740, 748, 751	332, 603, 679,	\includecolorgraphics
f inal (option) 4	684, 685, 686, 687 11, 332, 738
\footins 131	\HSelect 9, 705	\includegraphics ..
\footnotesize . 173,	\hskip 143, 739, 740
175, 206, 504, 588	152, 598, 602,	\indent 597, 601, 605, 609
\footrulewidth 160	664, 730, 731, 732	\InputIfFileExists . 51
\footskip 136	\hss 153, 734	\interlinepenalty . 591
\formatdate 7, 349	\Hy@AlphNoErr . 628, 640	\issuenumber 7, 234, 367
\fulladdress 5, 218, 245	\Hy@colorlink 709	\item 408, 506, 664
\fullpageref 9, 719	\Hy@colorlinksfalse 708	\itemindent 404
\fullref 9, 715	\Hy@endcolorlink .. 710	\itemize 147
\fullwidthdisplay . 406	\hyperref . 714, 718, 719	\itshape .. 117, 585,
\funding 11, 741	\hypersetup 85, 88, 91,	620, 624, 627, 665
	495, 514, 549, 568	
G	\HyPsd@@@pageref .. 198	
\g@addto@abstract .		J
..... 381,		\jfm 12, 684
388, 389, 391, 392		\jobname 434
\g@addto@macro	I	
.... 246, 247,	\if@aom@doiMMXVI 41, 675	
	\if@aom@manuscript@mode	
	32, 87, 162, 174,	K
	186, 689, 695, 705	\kern 332

```

\keyword ... 6, 221, 333 \newcommand 327, 332, 689, 701, 705, 715, 716, 717, 718, 719, 738, 741
L
\labelenumi ..... 143 \newif ..... 32, 35, 38, 41, 44, 47, 272
\labelitemi ..... 152 143, 145, 152, 664 \newsavebox ..... 163
\labelsep ..... 142, \newtheorem ..... 10, 655 \newtheoremlstyle ...
\labelwidth ... 145, 402 \newwrite ..... 430
\langugename ..... . 385, 386, 389, 392, 442, 443, 485 \nobreak 587, 589, 592, 597, 601, 603, 605, 607, 609, 610
\LARGE ..... 492 \noexpand . 104, 105, 107, 108, 109, 111
\leavevmode ..... 60 \nolinkurl ..... 603
\leftmargin 144, 152, 403 \normalfont ... 401, 408, 617, 620, 624, 627, 643, 646, 650, 654, 662
\leftmargini ..... . 143, 144, 145 \normalparindent .. 404
\let . 10, 57, 59, 64, \normalsize ... 125, 401
117, 118, 126, \number ..... 630, 633
335, 336, 337, 338, 357, 359, 361, 363, 365, 406, 412, 413, 414, 415, 489, 532, 541, 544, 556, 641, 671, 727
\lhead ..... 187
\linebreak ..... 516
\linespacing ... 125, 616, 619, 623, 626, 644, 647, 651
\list ..... 151, 402
\listparindent .... 404
\llap ..... 153
\LoadClass ..... 58
\long ..... 24, 382, 383
\loop ..... 166

M
\m@th ..... 724
\makelabel ..... 153
\MakeLowercase .... 574
\maketitle . 6, 394, 396
\MakeUppercase .... 183
manuscript (option) .. 4
\marginpar ..... 692
\marginparwidth ... 692
\mathaccent ..... . 106, 107, 110, 111
\MessageBreak ..... 114
\mr ..... 12, 684
\mrnumber .. 7, 242, 416

N
\NeedsTeXFormat .... 1

\newcommand 327, 332, 689, 701, 705, 715, 716, 717, 718, 719, 738, 741
\newif ..... 32, 35, 38, 41, 44, 47, 272
\newsavebox ..... 163
\newtheorem ..... 10, 655
\newtheoremlstyle ...
\newwrite ..... 430
\nobreak 587, 589, 592, 597, 601, 603, 605, 607, 609, 610
\noexpand . 104, 105, 107, 108, 109, 111
\nolinkurl ..... 603
\normalfont ... 401, 408, 617, 620, 624, 627, 643, 646, 650, 654, 662
\normalparindent .. 404
\normalsize ... 125, 401
\number ..... 630, 633

O
\oddsidemargin .... 129
olddoi (option) ..... 4
oldkeywords (option) .. 4
\oldsubsections .. 8, 621
\openout ..... 434
options:
10pt ..... 4
11pt ..... 4
12pt ..... 4
8pt ..... 4
9pt ..... 4
doi2016 ..... 4
draft ..... 4
final ..... 4
manuscript ..... 4
olddoi ..... 4
oldkeywords ..... 4
printscheme ..... 4
screen ..... 4
\or 120, 121, 122, 123, 124, 352, 353, 354
\orcid .. 5, 216, 327, 608
\overline ..... 10, 126

P
\p@ 405, 491, 504, 662, 728
\p@equation ..... 722
\PageIndex ..... 15

Q
\qed ..... 661

R
\r@LastPage ... 436, 440
\raggedright ..... 692
\received .. 7, 223, 356

```

```

\RecordChanges .... 17 \skip ..... 134 \title ..... 5, 209
\ref ..... 714, 718 \Small ..... 408 \topsep ..... 662
\relax ... 56, 68, 69, \small ..... 517, 688 \topskip ..... 131
142, 165, 292, \space ..... 80, \trivlist .... 503, 663
293, 301, 340, 283, 355, 396, \tw@ ... 105, 109, 731, 732
351, 394, 406, 435, 521, 598, 602
411, 491, 500, \specialdigits .... 116
504, 506, 532, \start@page 194, 196,
659, 662, 690, 372, 374, 437, 460
702, 744, 745, 748 \startpage ..... 7, 239, 371, 379
\renewcommand ..... 160, 161, \stepcounter ..... 721
249, 288, 318, \string ... 76, 268, 435
322, 614, 655, 688 \subject ... 7, 222, 335
\renewenvironment ..... 147, 410, 660 \subsection .... 618, 622
\repeat ..... 167 \subsubsection .... 625
\repeatedauthors ... 670 \surname ... 5, 219, 245
\RequirePackage ... \symAMSb .... 106, 110
82, 83, 95, 102, 113
\reset@font ..... 77
\revised ... 7, 224, 356
\rightmargin ..... 403
\romannumeral . 150, 374

S
\savebox ..... 164
screen (option) .... 4
\scriptsize 166, 172,
181, 183, 191, 692
\scshape ..... 517, 589, 598, 645
\seconded ... 7, 229, 413
\section ..... 615
\sectionname ..... 641
\setbox ..... 398
\setcounter ... 371, 373
\setlength 127, 128,
131, 132, 133,
134, 135, 136,
137, 138, 158, 159
\settowidth ... 143, 152
\shortauthors ... 6,
183, 259, 260, 262
\shorttitle ..... 172
\sishape ..... 117, 644, 649, 653

T
\tabskip ..... 726, 730, 733, 735
\tagform@ ..... 718
\TC@level .... 706, 707
\tempa ..... 195,
197, 198, 200, 202
\tempb ..... 196, 202
\textbf ..... 192
\textcopyright ..... 427
\textheight ..... 127
\textit ..... 118
\textsi ..... 118
\textstyle ... 104, 108
\textup ..... 718
\textwidth ..... 127
\thanks ... 6, 220, 502
\thanks@warning ... 502
\thankses ..... 540
\the ..... 150, 166, 355
\theequation ..... 722
\theHsection ..... 640
\thepage 80, 173, 175, 206
\thesection ..... 642
\thmname .. 646, 650, 654
\thmnote .. 646, 650, 654
\thmnumber 646, 650, 654
\thr@@ ..... 734

U
\undefined ... 385, 442
\underline ..... 166
\unskip ..... 590,
594, 598, 602, 606
\upshape 153, 276, 507,
527, 642, 648, 652
\url ... 607, 610, 676, 681
\urladdr 5, 215, 322, 604
\urlstyle ..... 94
\usebox ... 176, 179, 188
\usepackage 9, 11, 12, 13

V
\value 629, 630, 632, 633
\version ... 7, 232, 415
\vgline ..... 400, 401
\volumenumber 7, 233, 366
\vtop ..... 398

W
\wd ..... 105, 109
\widebar ..... 9, 10, 126
\widehat ..... 9, 104
\wideparen ..... 9
\widering ..... 9
\widetilde ..... 9, 104
\widetriangle ..... 9
\widowpenalty ..... 139
\write ..... 76

X
\xdef ..... 104, 108, 512

Z
\z@ ..... 104, 105,
108, 109, 138,
373, 402, 405,
616, 639, 725, 734
\z@skip ..... 730, 735
\zbl ..... 12, 684
\zblnumber . 7, 243, 416

```